

IS-310/IS-320

IntelliSense

IntelliSense's Request-to-Exit (RTE) sensors offer basic and full-featured models to suit every access control application. The quick-install sensors are extremely flexible, provide a generous amount of wiring room and contain built-in internal shutters to guard against tampering.

The standard (IS-310) and full-featured (IS-320) units both share the same look, making them the ideal choice for retrofits as well as new installations.



FEATURES:

- Adjustable relay time
- Micro-based signal processing
- Adjustable shutters provide precise target area
- Available in white or black

Advanced features on IS-320 include:

- Piezo sounder
- Door contact input
- Reader/keypad/keyswitch input
- Remote arming and sounder inputs
- Monitor Door and Fail Safe/Secure modes

SPECIFICATIONS:

- **Range:** From 5.5' x 2' up to 8.4' x 15.8' depending on mounting height
- **Mounting Height:** 7' to 15'
- **Detectable Walk Rate:** 0.5' – 10'/sec
- **Signal Processing:** RTE and Security modes
- **Temperature Compensation:** Advanced dual-slope
- **Alarm Relay:** Two Form C outputs
- **Input Voltage:** 12-24 volts AC or DC
- **Standby Current:** 35mA
- **Indicators:** Green (ready) LED
- **Operating Temperature:** 14° F to 122° F
- **Dimensions:** 7" L x 2" H x 2" D
- **Accessories:**
 - IS-310WHTP - Single gang trim plate for IS-310/320 white
 - IS-310BLTP - Single gange trim plate for IS-310/320 black

ORDERING:

| Part No. | Description |
|----------|--------------------------------|
| IS-310WH | Request-to-Exit Sensor (White) |
| IS-310BL | Request-to-Exit Sensor (Black) |
| IS-320WH | Request-to-Exit Sensor (White) |
| IS-320BL | Request-to-Exit Sensor (Black) |

Request-to-Exit PIR



1230 S. Hurstbourne Pkwy.
Suite 100
Louisville, KY 40222
1-800-467-5875

ADEMCO
A Honeywell Company