

# ADPRO® iFT™ Gateway

4 Channel Video Transmission

Introducing the ADPRO iFT Gateway, the entry level member of the XO-enabled NVR+ portfolio, offering full remote monitoring features that security professionals have come to trust from ADPRO.



iFT Gateway, the next generation of low cost IP video remote alarm transmission, offers 4 IP channels of video transmission with the option to easily add 4 channels of ADPRO analytics and event recording via MicroSD card. This platform is ideal for local retail, residential and remote site applications.

This IP video multi-service platform runs the powerful XO Security+ operating system software offering full remote monitoring features such as arming/disarming, event quad pictures with the most reliable and secure transmission of alarms unlike competitive solutions that rely on insecure email transmission of alarms.

The iFT Gateway optimizes bandwidth use for high quality transmission by multi-stream camera connections, adapting video transmission to the available bandwidth. Add up to 4 channels of ADPRO analytics and deliver instant remote monitoring solutions.

Designed for remote operation, ADPRO iFT gateway supports the viewing of video and events through networked clients, including CMS and VMS software and the iTrace mobile application for 24/365 monitoring and control wherever you are. ADPRO Xchange2 also allows you to remotely manage the licensing of additional IP and analytics channels for ultimate flexibility.

## FEATURES AND BENEFITS

- P2P connection available for easy and flexible remote connection
- End to end secure streaming<sup>(3)</sup> where video is encrypted (HTTPS) from the camera right through to the viewer to avoid tampering (when connecting with 30s and 60s cameras)
- Integration with the Honeywell 30/60 Series IP cameras, iFT gateway can be used as part of video systems which comply with NDAA (National Defense Authorization Act) 2019, Section 889.
- Offers up to 4 IP channels with the option to add the most advanced analytics for use internally and externally to all 4 camera channels
- Support for all major camera brands: ACTI, Arecont, Avigilon, Axis, Bosch, Brickcom, Hikvision, Hikvision AVE, Honeywell (Performance series<sup>(1)</sup>, eQuIP Series<sup>(1)</sup>, eQuIP Series 2019<sup>(2)</sup>, HDZ Series<sup>(1)</sup>, 30/60 Series<sup>(2)</sup>), JVC, Panasonic, Pelco, Samsung, Sanyo, Sony, Uniview<sup>(2)</sup>, VISTA<sup>(2)</sup>, and FLIR<sup>(2)</sup>, and support ONVIF Profile S & T compliant IP cameras
- Network or USB I/O modules providing the option for fully monitored inputs
- Video event recording is possible using an optional MicroSD card
- 2 way audio is available via 2 way audio compatible cameras
- Optional advanced integrated video analytics; select ADPRO IntrusionTrace or ADPRO LoiterTrace analytics for each camera channel
- Xchange2 for adding video and VCA licenses
- Bulk firmware upgrade remotely
- Supporting new licensing type switchable between LoiterTrace and IntrusionTrace.
- Mobile app for remote monitoring, verification, and control
- CMS command and control platforms: Video Central Platinum (VCP) and iOS/Android iTrace App
- Open platform: easy integration with third-party software (XO-SDK)
- Superior detection and low false alarm rate with the highest quality of protection at an affordable price.
- Multiple applications:
  - Local Retail Stores
  - Residential
  - Temporary Protection
  - Small Remote Sites
- Highest site protection: powerful new XO 5 delivering intrusion and loitering analytics
- Reliability: ADPRO proprietary transmission protocol is 100%reliable with guaranteed alarm reception by acknowledgment and redundant transmission, including Site Pulse protocol life check
- Efficient video compression and multi-streaming for optimal bandwidth usage while providing the highest quality video for recording and viewing
- Low Cost: 4 IP cameras with optional 4 analytics channels
- Easy management of multiple remote sites improves efficiency and reduces personnel cost
- Full remote site surveillance and control, extending human guard surveillance
- Speed: rapid assessment of video alarm images enables quick identification of the alarm cause, optimizing real-time intervention while reducing expensive nuisance alarm responses
- User-friendly XO client for easy configuration and management
- Advanced camera tamper enabled
- 360° camera support + image de-warping: see everything, everywhere, always

(1) The Honeywell Performance, eQuIP, and HDZ series IP cameras are supported from version XOa 3.2.33.

(2) The Uniview, Honeywell eQuIP Series 2019 and 30 Series, VISTA, and FLIR cameras are supported from version XO 4.5.

(3) When secure streaming is enabled. Audio back from XO Client/ CMS to cameras will be disabled.

**Honeywell**

# ADPRO® iFT™ Gateway Specifications

OPERATIONAL	
OPERATING SYSTEM	ADPRO® XO™ Security Operating System, Linux based
VIDEO INPUT	4 IP cameras
VIDEO OUTPUT	N/A
VIDEO COMPRESSION	H.264 and H.265 - camera dependent using XO 4.2 and onward
VIDEO RESOLUTION AND IPS	4 analytics streams max 4 CIF/5fps max. 1Mbps, with analytic on each channel. 4 streams max. 1920x1080/25fps max. 2Mbps.
WIFI	802.11 b/g/n 2.4 Ghz Broadcom AP6212 module
BANDWIDTH CAPACITY	4 streams 1920x1080/25fps max. 2Mbps
BANDWIDTH MANAGEMENT	Configurable variable or constant bitrate / Configurable bandwidth limiter
AUDIO INPUT	Via approved cameras
AUDIO OUTPUT	Via approved cameras and local 2 V output impedance 600-Ω
ALARM INPUTS	Via XO I/O interface USB module: up to 20 Via Network I/O module with PoE: from 4 up to 128*
RELAY OUTPUTS	Via XO I/O interface USB module: up to 8 Via Network I/O module with PoE: from 4 up to 128
USB PORTS	2
WEB SERVER	XO client - integrated web client application (ActiveX)
ETHERNET	10/100 BASE-T, autodetection, full duplex, RJ45
RECORDING TYPE	Event recording on MicroSD card (not supplied), min. capacity 32 GB
IP CAMERA INTEGRATION	Brand specific, generic, support ONVIF Profile S & T** compliant IP cameras
MANAGEMENT	Web client interface (XO client), ADPRO VideoCentral Platinum, third-party software (SDK available) and iOS/Android iTrace App.
POWER SUPPLY	DC 5V/2A supplied via universal 120/240 VAC power supply
OPERATING TEMPERATURE	0-70 °C Storage Temp -10 to 70 °C
HUMIDITY	Humidity 5-90 % non-condensing
WARRANTY	Up to 2 years for return at customer cost of postage. No advance replacement.
DIMENSIONS (W X H X D)	101.6 x 101.6 x 23.6 mm
ANALYTICS	Advanced camera tamper with the option to add up to 4 advanced analytic channels of IntrusionTrace™ or LoiterTrace™, (separate datasheets available). Motion detection and post motion detection are included in iFT Gateway.
MOBILE APP	iTrace

## ORDERING INFORMATION

66000000	ADPRO iFT Gateway 4IP-No Storage-No inputs/outputs
66000004	ADPRO iFT Gateway 4IP-No Storage-No inputs/outputs + 4 Video Analytics

The contents of this document are provided on an "as is" basis. No representation or warranty (either express or implied) is made as to the completeness, accuracy or reliability of the contents of this document. The manufacturer reserves the right to change designs or specifications without obligation and without further notice. Except as otherwise provided, all warranties, express or implied, including without limitation any implied warranties of merchantability and fitness for a particular purpose are expressly excluded.

The Sooner You Know, VESDA-E, VESDA, ICAM, ECO, OSID, HeiTel, ADPRO, IntrusionTrace, LoiterTrace, ClientTrace, SmokeTrace, XOa, XOh, iTrace, iCommand, iRespond, iCommission, iPIR, and FMST are trademarks and/or registered trademarks of Honeywell and/or its subsidiaries in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Your use of this document does not constitute or create a licence or any other right to use the name and/or trademark and/or label.

### Find out more:

[www.security.honeywell.com](http://www.security.honeywell.com)

### Honeywell Commercial Security

715 Peachtree St. NE  
Atlanta, GA 30308  
1.800.323.4576  
[www.honeywell.com](http://www.honeywell.com)

HSV-IFTGTW-07-US(0221)DS-Z  
© 2021 Honeywell International Inc.

## XO 5

The XO Security Operating System expands the feature-rich, multiservice capability of the ADPRO NVR+ platforms. XO enables an iFT Gateway to offer 4 IP channels of video transmission with the option to easily add 4 channels of ADPRO analytics and event recording via MicroSD card. This allows a customer to leverage ADPRO analytics for intrusion and loitering detection, and building management capabilities while providing immediate remote response. It provides live 24/365 unbreakable transmission of very high quality video events to remote monitoring stations; providing deterrence through multi-level response, including audio, lighting/door controls, as well as first responder dispatch. XO provides the first technology solution to effectively augment human guard security with intelligent and accurate detection, cost effectively with higher reliability.

### ADPRO Analytics

The following analytics are available for each camera channel:

- IntrusionTrace: outdoor video verified perimeter detection for sterile zone monitoring.
- LoiterTrace: video verified loiter detection for indoor and outdoor applications.

The New Analytics Feature for ADPRO allows the customer to order a VCA License with the ability to switch each channel individually between LoiterTrace and IntrusionTrace at any time, saving the need to purchase separate licenses.

**Honeywell**