

HMM9

9 INCH MONOCHROME MONITOR

Honeywell Video's HMM9 is a compact, high quality 9-inch monochrome monitor that is ideal for video surveillance applications where single camera viewing on dedicated monitors is a requirement. The HMM9 features a sturdy housing and delivers sharp images with over 800 TV lines of resolution. Unlike conventional monitors, it has convenient recessed front panel controls making it easy to set up and adjust, while restricting movement caused by accidental contact.

Installers can easily switch between EIA and CCIR video formats. An illuminated green LED beside the power button confirms that power is being supplied to the monitor. The monitor features a latching power switch which remains in its set position – either on or off – eliminating the need to turn the monitor back on in the event of a power loss.

The HMM9 has a composite BNC connector with looping output. The BNC connectors are auto terminating, eliminating the need for installers to set termination switches when using for loop-through video.

The HMM9's compact size and attractive styling are ideal for rack mount use or in areas where space is a premium. Honeywell Video's HMM9 can be easily rack mounted using an optional single rack mount kit (HMM9RK1), or a dual rack mount kit (HMM9RK2).

Features:

- >1000 TVL (at center)
- Convenient recessed front panel controls
- Heavy-duty metal cabinet
- EIA or CCIR selectable
- Video loop-through with automatic termination
- Latching power switch
- Single or dual rack mountable

HMM9



HMM9X



HMM9

SPECIFICATIONS:

Technical	
Picture Tube:	9" (23 cm) diagonal
Resolution:	1000 TV lines (at center)
Video Standard:	EIA/CCIR
Deflection:	90° angle
Electrical	
Power Source:	90 to 264 VAC, 60 Hz/50 Hz
AC Input Connector:	IEC 320 type connector for AC input
Power Cable:	NEMA 5-15P, UL
Power Consumption:	15 Watts
Scanning Frequency	
Horizontal:	60 Hz: 15.734 KHz; 50 Hz: 15.625 KHz
Vertical:	60 Hz: 59.94 Hz; 50 Hz: 50Hz
Video Input:	One pair of BNC connectors for loop-through operation, auto terminating; Level: 1Vp-p (75 Ohms); Impedance: 75 Ohms/Hi-Z
Linearity:	Horizontal: 10% maximum; Vertical: 10% maximum
Active Area Display:	Horizontal: 10% overscanning; Vertical: 13% overscanning
Controls	
Front:	•H-Hold •V-Hold •Bright •Contrast• Power Switch
Back:	•V-linearity •V-height •EIA/CCIR selector switch
Environmental	
Operating Temperature:	32° F to 104° F (0° C to 40° C)
Operating Humidity:	0% to 90% (noncondensing)
Mechanical	
Dimensions (W x H x D):	8-11/16" x 9-1/16"x 9-3/4" (220 mm x 230 mm x 333 mm)
Weight:	10lbs (4.5 kg.)
Shipping Weight:	12.5 lbs (5.7 kg.)
Regulatory	
Emissions:	FCC Part 15, Class B, Canada ICES-003
Safety:	UL: UL1950, cUL: CSA C22.2 No. 950 DHHS Rules 21

Ordering	
HMM9	9" Monochrome Monitor, black cabinet
HM9X	9" Monochrome Monitor, grey cabinet

Note: Honeywell reserves the right, without notification, to make changes in product design or specifications.

Honeywell Security

Honeywell Video Systems
2700 Blankenbaker Pkwy, Suite 150
Louisville, KY 40299
800 796 CCTV
www.honeywell.com

L/HMM9a/D
September 2005
©2005 Honeywell International Inc.