

IR-HK-2

HandKey CR Hand Geometry Reader

Biometric hand geometry reader, 512 users. Operating temperature range: 32° to 113° F (0° to 45° C) with 20 to 80% relative humidity non-condensing. Dimensions: 11.65" H x 8.85" W x 8.55" D (29.6cm H x 22.3cm W x 21.7cm D).



IR-HK-2-ICLASS

HandKey CR Hand Geometry Reader with iClass Smart Card Reader

Biometric hand geometry reader including an iClass/OmniClass smart card reader. Templates are stored on the smart card.

IR-HK-2-PROX

HandKey Hand Geometry Reader with HID Proximity Reader

HG-4 HandKey biometric reader with internal HID proximity reader.

IR-HK-CM

HandKey II Standalone Hand Geometry Reader

Standalone biometric hand geometry reader with two auxiliary and a door egress input and three auxiliary outputs, for interior usage, 512 users.



IR-EN-200

Ethernet Module for HG4

10Base-T with RJ-45 connector. Must be ordered at time of purchase in order to be installed at the factory. Cannot be installed in the field.

HGHNR5

Handnet for Windows®, 5 Reader License (Includes RS-485 Interface)

HandNet for Windows® software is used to link HandKey units into an integrated system. All alarms and transactions will report back to a central computer in real time, making monitoring easy and efficient. System user activity reports are easily created and printed. Up to 5 readers supported.

ALSO AVAILABLE: HGHNR25

Handnet for Windows®, 25 Reader License (Includes RS-485 Interface)

Up to 25 readers supported.

HGHNRUNL

Handnet for Windows®, Unlimited Reader License (Includes RS-485 Interface)

Unlimited number of readers supported.