# Alarm Communications | SIRENS AND SOUNDERS

# **SIRENS**

#### MS=N

## Internal Multi-siren (No Logo)

Voltage: 9-18 VdcSiren: 107dB

• Operating Temp: -20 to +60°C

• Humidity: 5%-95%

Dimensions: 110x95x46mm (HxWxD)Housing: White, durable ABS plastic

# **EXTERNAL SOUNDERS**



#### **RESON8 SAB**

# White/Blue Bell Box has 115dB sounder output

- Fully integrated sounder/strobe
- Self-activating cut-off timer
- Aesthetic enclosure
- Dual Anti-Tamper operation
- NiCad Battery Backup and twin LED status indication
- EN50131-1 Security Grade 2, Environmental Class IV.



#### AG6/WB

### ActiveGuard External Siren

- Sound output of 110dB
- · High impact polycarbonate moulding
- One standard built-in wrap around strobe lens
- Horizontal and vertical mounting
- Front and rear tamper
- Multi-colour options
- NiCad back-up battery included
- Piezo sounder



#### AG8/WB

### **ActiveGuard External Siren**

- Sound output of 116dB
- High impact polycarbonate moulding
- One standard built-in wrap around strobe lens
- · Horizontal and vertical mounting
- Front and rear tamper
- Multi-colour options
- NiCad back-up battery included
- Two Piezo sounders
- Diagnostic LEDs
- Silent start-up
- Dual tones
- Current flow monitor



# AG3/WB

## **ActiveGuard External Sounder**

- Sound output of 116dB
- High impact polycarbonate moulding
- 2 Watt Xenon Strobe Tube, Alternating LEDs
- NiCadback-up battery included
- Multi-colour options
- Front & Rear tamper
- Sweeper Sounder sound
- EN50131 Security Grade 3, Environmental Class IV.