

## Indala®

### FlexPass® Proximity Credentials



Indala®'s high-quality line of 125 kHz FlexPass® Readers combines intelligent programming technology with a range of stylish cover designs. The FlexPass portfolio includes PVC printable cards, clam shell cards, keyfobs, stickers, and readers.

The FlexISO™ proximity card is truly a "credit card" thin access credential, and is ISO 7813 compliant with a nominal thickness of 0.03 inches (0.76 mm). The FlexISO™ has the ability to contain multiple ID technologies in a single credential. It is also available with a magnetic stripe for use with other systems, such as cafeteria vending, copy machines and fuel dispensing. Digital photos and graphics can be printed directly over the FlexISO™'s front surface by using a dye-sublimation printer. Bar codes can be imaged onto the card for systems tracking time-and-attendance for job costing.

The FlexCard™ proximity card is "credit card" size, features beveled edges, and at a thickness of only 0.065 inches (1.8mm), is one of the thinnest clam shell proximity cards available. Flexible and light enough to be carried in a purse or wallet, the card can also accept photo-flap and direct-print adhesive backed ID badge overlays.

The FlexKey™'s contemporary design enables it to be easily attached to a key ring, badge clip, or badge lanyard. Built to withstand harsh operating environments, FlexKey™'s rugged double-sealed construction also allows for customization.

The new, innovative FlexTag™ can turn your plastic ID badge into a proximity credential! Effortlessly upgrade from mag stripe or barium ferrite technology, or add prox to your smart card, by simply attaching the small, circular FlexTag™ to your existing card. The FlexTag™ will also adhere to any non-metallic device, such as a cell phone or PDA, to create an instant proximity badge.

## FEATURES

- Availability of custom options including: custom artwork, UV ink, surface or embedded hologram, and an added contact smart chip modules
- FlexSecur™ technology provides an added level of access system security through a verification process at the reader wherein the entire data field is encoded on the card to inhibit undesired card duplication



## FlexPass® Proximity Credentials

### SPECIFICATIONS

	FlexCard™ Clamshell Cards	FlexISO™ PVC Cards	FlexKey™ Keyfobs	FlexTag™ Stickers
<b>Dimensions</b>	3.38" H x 2.13" W x 0.065" T (8.6cm H x 5.4cm W x .165cm T)	3.38" H x 2.12" W x 0.03" T (8.6cm H x 5.4cm W x .076cm T)	1.725" H x 1.197" W x 0.215" T (4.38cm H x 3.04cm W x .546cm T)	2.285" diameter x 0.070" T (5.80cm diameter x 0.178cm T)
<b>Finish</b>	White	White, printable	Blue	Gray
<b>Credential Construction</b>				Lexan
<b>Slot Punch</b>	Pre-punched, vertical	Vertical or Horizontal with locations indicated on card	Yes	N/A
<b>Max Read Range<sup>1</sup></b>				
<b>Classic</b>	4" (10cm)		3.5" (8.89cm)	3" (7.62cm)
<b>Slim or Wall Switch</b>	5" (12.7cm)		3.5" (8.89cm)	3" (7.62cm)
<b>Mid Range</b>	12" (30.5cm)		8" (20.32cm)	7" (17.78cm)
<b>Long Range</b>	28" (71cm)		15" (38.1cm)	15" (38.1cm)
<b>Operating Temperature</b>	-22° to 149° F (-30° to 65° C)	32° to 122° F (0° to 50° C)	22° to 149° F (-30° to 65° C)	-50° to 160° F (-45° to 70° C)
<b>Operating Humidity</b>	10 to 85% relative humidity			
<b>Warranty<sup>1</sup></b>	1 year			

<sup>1</sup> See Honeywell Access Systems' Sales Policy for complete warranty details.

Indala® is a registered trademark of Assa Abloy.

FlexPass® is a registered trademark of Indala Corporation.

FlexISO™, FlexCard™, FlexKey™, FlexTag™, and FlexSecur™ are trademarks of Indala Corporation.

### ORDERING

- PX-121-I** FlexCard™, 26-bit Wiegand Format
- PVC-I-5** FlexISO™ Card, 26-bit Wiegand Format
- PVC-I-6** FlexISO™ Card, 26-bit Wiegand Format, plus magnetic stripe
- PVC-I-7** FlexISO™ Card, 26-bit Wiegand Format, printable on both sides
- PX-115-I** FlexKey™ Keyfob, 26-bit Wiegand Format

**For more information:** [www.honeywell.com/security/uk](http://www.honeywell.com/security/uk)

#### Honeywell Access Systems UK

Charles Avenue  
 Burgess Hill  
 West Sussex.  
 RH15 9UF  
 01444 251180  
 01444 871074  
[www.honeywell.com/security/uk](http://www.honeywell.com/security/uk)

