

V-SMART-ICLASS

V-Smart™ with HID iClass 13.56MHz Reader

V-Smart with HID iClass/OmniClass 13.56MHz reader is a dual factor reader for security and access control. It verifies the live fingerprint against the template stored in the 16K smart card and allows for Wiegand communication formats up to 64 bits. Operating temperature range: 32° to 140° F (0° to 60° C). Dimensions: 5.1" H x 4.7" W x 2.5" D (13cm H x 11.8cm W x 6.4cm D).



ALSO AVAILABLE:

V-SMART-MIFARE

V-Smart with Mifare 13.56MHz Reader

V-TENC-W

V-Smart Outdoor Enclosure with Window

Dimensions: 11.5" H x 8.07" W x 5.5" D (29.2cm H x 20.5cm W x 14.0cm D). Lid lifts up and is 11.25" H 9.25" W x (28.6cm H x 23.5cm W). Reader not included.



V-STATION-BASE

V-Station Base Model with LCD Display

Up to 3,550 Templates

A fingerprint biometric terminal for use with security and access control systems, V-Station includes LCD display and keypad. The fingerprint is verified against the template stored in the terminal after it has been chosen by PIN or external Wiegand device. Up to 3,550 templates stored in each terminal. Operating temperature range: 32° to 140° F (0° to 60° C). Dimensions: 5.63" H x 6.63" W x 2.63" D (14.3cm H x 16.8cm W x 6.7cm D).



V-STATION-BASE-S

V-Station Base Model with LCD and Display, Search,

Up to 200 Templates

Includes LCD display, keypad and fingerprint identification. Identifies the user from up to 200 templates stored in the terminal without use of card or PIN.



V-STATION-PROX

V-Station Base Model with LCD & HID 125kHz Proximity Reader

A fingerprint biometric terminal for use with security and access control systems, V-Station includes LCD display, keypad and HID 125kHz proximity reader. The fingerprint is verified against the template stored in the terminal after it has been chosen by PIN or internal proximity reader. Up to 3,550 templates stored in each terminal. Operating temperature range: 32° to 140° F (0° to 60° C). Dimensions: 5.63" H x 6.63" W x 2.63" D (14.3cm H x 16.8cm W x 6.7cm D).



ALSO AVAILABLE:

V-STATION-ICLASS

V-Station Base Model with LCD & HID iClass Reader

Includes LCD display, keypad & HID iClass/OmniClass Reader. The fingerprint is verified against the template stored in the 16K iClass or OmniClass smart card. Unlimited users as the template is stored and transported on the card.

V-STATION-MIFARE

V-Station Base Model with LCD & Mifare™ Reader

Includes LCD display, keypad and Mifare reader. The fingerprint is verified against the template stored in the Mifare contactless smart card. Unlimited users as the template is stored and transported on the card.

V-NENC

V-Station™ Outdoor Enclosure Only

Dimensions: 11.5" H x 9.25" W x 5.5" D (29.2cm H x 23.5cm W x 14.0cm D). Lid lifts up and is 11.25" H x 9.25" W (28.6cm H x 23.5cm W).

ALSO AVAILABLE:

V-NENC-HT

V-Station Outdoor Enclosure with Heater

V-NENC-W

V-Station Outdoor Enclosure with Window

V-NENC-W-HT

V-Station Outdoor Enclosure with Window and Heater

