

IR-1200



IDIS Ready to Install with IDIS VMS Enterprise Server

- Pre-installed with IDIS Solution Suite VMS
- 1,024Mbps (128MBps) maximum recording bandwidth per server
- Equipped with RAID 5, RAID 6 recording, Hot swappable
- Tested and validated with IDIS Solution Suite up to 256 Full HD H.264/H.265 IP cameras
- Redundancy of power for mission-critical reliability
- Supports H.264, H.265 compression, and Intelligent Codec
- Supports up to 256 Full HD cameras in real-time for enterprise-level surveillance systems
- Complete compatibility with IDIS components: IP cameras, analog DVR, DirectCX TVR, DirectIP NVR, and encoders
- Supports Onvif Profile S, Axis, Panasonic, etc.

SPECIFICATIONS

General	
Operating System	Microsoft® Embedded Windows Server 2022 IoT Std
Processor	Intel® Xeon® Processor silver 4410Y 2G, 12C/24T
Memory	16GB RAM (1 x 16GB DDR5-4800MT/s RDIMM)
Recording	
Max. Throughput	Up to 1024Mbps (128MBps)
Mechanical	
Unit Dimensions (W x H x D)	482.0mm x 86.8mm x 721.62mm (18.97" x 3.41" x 28.4")
Unit Weight	Max 28.6kg (63.0 lbs)
Electrical	
Power Input	100-240V AC, 50/60Hz
Environmental	
Operating Temperature	10° to 35°C (50° to 95°F)
Operating Humidity	0% ~ 80%



PRODUCT IMAGE



DIMENSIONS

(Unit - mm)

