

MVF-60/90

Duplex 6ch / 9ch Multiplexer



The MVF-60/ 90 series Multiplexers have a feature of monitoring the six (MVF-60) and nine (MVF-90) camera picture, display Quad (A/ B), Six (MVF-60) and Nine (MVF-90) split views, video output to VCR while sequentially switching the pictures from cameras, as well as monitoring of desired channel picture selected from the recorded video data in VCR's or DVR's.

- Full Duplex operation
- B/W & Color camera can be used
- Auto sequential operation with no switching noise
- Looping Outputs
- Up to 8 letters title setting (each camera)
- Alarm In/ Out
- Two Independent Monitor Outputs
- On-Screen Alphanumeric Display
- Video Loss alarm
- RS-232C or RS-485 interface (optional)
- 1/60 sec. Refresh (Real-Time)

SPECIFICATIONS

MVF-60

MVF-90

Video input signal:	NTSC	NTSC
Camera video input:	6 inputs, BNC, 75 Ohm (VBS.VS 1.0V p-p)	9 inputs, BNC, 75 Ohm (VBS.VS 1.0V p-p)
Video Loop output:	6 outputs, BNC, 75 Ohm (VBS.VS 1.0V p-p)	9 outputs, BNC, 75 Ohm (VBS.VS 1.0V p-p)
VCR video input:	1 inputs, BNC, 75 Ohm (VBS.VS 1.0V p-p)	1 inputs, BNC, 75 Ohm (VBS.VS 1.0V p-p)
VCR video output:	1 outputs, BNC, 75 Ohm (VBS.VS 1.0V p-p)	1 outputs, BNC, 75 Ohm (VBS.VS 1.0V p-p)
Monitor video output:	1 outputs, BNC, 75 Ohm (VBS.VS 1.0V p-p)	1 outputs, BNC, 75 Ohm (VBS.VS 1.0V p-p)
Alarm/ Remote signal input:	6 inputs, D-SUB connector, No-voltage (make / break) contact, TTL level Pulse width: 100 mSec. or more Pulse interval: 200mSec. or more	9 inputs, D-SUB connector, No-voltage (make / break) contact, TTL level Pulse width: 100 mSec. or more Pulse interval: 200mSec. or more
Alarm signal input:	1 input, Terminal block, open collector	1 input, Dsub connector, Open collector
Trigger signal input:	1input, Terminal block, TTL positive/ negative Pulse width: 7.0 mSec. or more Pulse interval: 50.1mSec. or more	1input, Dsub connector, TTL positive/ negative
Video output display:	Single, Quad, A/B, Six-part split view display 1/60-sec. refresh (real-time)	One, Quad, A/B, Nine-part split view display 1/60-sec. refresh (real-time)
VCR video switching:	1 to 999 seconds (single display)	1 to 999 seconds (single display)
Title display:	Up to 8 letters for each channel	Up to 8 letters for each channel
Operating Temperature:	32 to 104 F (0 to 40 C)	32 to 104 F (0 to 40 C)
Power supply:	120VAC +/- 10%, 60Hz	120VAC +/- 10%, 60Hz
Power consumption:	15W or less	16W or less
Dimensions:	13.8"(W) x1.7"(H) x11"(D) (350x44 x280mm)	16.5"(W) x 1.7"(H) x 9.9"(D) (420x44x252mm)
Weight	Approx. 6.7 lbs (3.0Kg)	Approx. 7.1 lbs (3.2Kg)
Accessories:	Power cable, Instruction manual, Spare fuse (Include in main unit)	Power cable, Instruction manual, Spare fuse (Include in main unit)

Ikegami Electronics (U.S.A.) Inc

■URL: <http://www.ikegami.com>

Headquarters	37 Brook Avenue, Maywood, NJ 07607 Phone: (201)368-9171 Fax: (201)569-1626
Westcoast office	20603 Earl Street, Torrance, CA 90503 Phone: (310)370-2400 Fax: (310)370-7131
Southwest office	Two Dallas Communications Complex, 6309 north O'Connor Road, Suite 117, Irving, TX 75039-3510 Phone: (972)869-2363 Fax: (972)556-1057
Midwest office	747 Church Road, Unit C4, Elmhurst, IL 60126 Phone: (630)834-9774 Fax: (630)834-8689
Southeast office	5200 N.W. 33 rd Avenue, Suite 111, Ft Lauderdale, FL 33309 Phone: (954)735-2203 Fax: (954)735-2227