



Integra® View Workstation

Control Center Performance. Intelligently Delivered.

The IndigoVision Integra® View Workstation is designed and configured for easy installation and enable the connection and management of multiple Integra® as a single site. The Integra View Mid Workstation supports up to four monitors and has an Intel® Core™ i7 quad core processor with ample 16GB RAM. Designed and pre-installed with Control Center Integra® View each workstation delivers guaranteed performance.

Key Features

Product Codes

COMPRESSION

H.264	 H.264	MJPEG	MPEG-4
--------------	-----------------------------------------------------------------------------------------------------	--------------	---------------

 AAC	 G.711
---------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------

OTHER

 DNA	
---------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------

PHYSICAL

 TOWER

Integra® View Workstations	Product Code
Integra® View Mid Workstation (G2) (unlimited channels)	980613

Specifications

General Specifications	Mid Workstation
Live Viewing Performance*	98 4SIF streams at 30fps, 18 HD streams at 30fps, 10 4MP streams at 30fps, 5 4K streams at 30fps
Playback Viewing Performance*	25 4SIF streams at 30fps, 11 HD streams at 30fps, 8 4MP streams at 30fps, 3 4K streams at 30fps
Operating System	Windows 10 64bit (IoT Enterprise Embedded 2016, Multi-Language)
Processor	Intel® Core™ i7 (3.2Ghz)
Memory	16GB DDR4 (2x8GB, 2666MHz)
O/S Hard Disk	256GB SSD (PCIe NVMe Class 40) plus 4TB 3.5in SATA
Network Interface	100/1000 BaseT RJ-45
Video Interface	Radeon Pro WX 2100 2GB Supporting up to three HD or three 4K monitor output or five HD monitors if using DisplayPort MST
Audio Interface	HDMI, Mic In, Headphone, Line In/Out
Form Factor	Mini Tower Form Factor Chassis
Dimensions/Weight	345mm (d) x 176.6mm (w) x 335mm (h) and 9.36Kg / 13.58in (d) x 6.95in (w) x 13.19in (h) and 20.63lb
Electrical	460W (100 to 240 VAC, 50/60 Hz, auto switching). 90% efficient PSU (80PLUS Gold Certified Certified) Energy Star compliant
Regulatory	EN 60950-1, IEC 60950-1, EN 55022, CISPR 22, EN 61000-3-2, EN 55024, IEC 61000-3-2 (Class D), EN 61000-3-3, IEC 61000-3-3, CISPR 24
Housing	Mild Steel Chassis and Polycarbonate Fascia
Temperature	Operating: 10 °C to 35 °C (50°F to 95°F) Storage: -40° C to 65° C (-40°F to 149°F)
Humidity	20% to 80% relative humidity (non-condensing)
Vibration	Operating: 5 Hz to 350 Hz at 0.0002 G ² /Hz Storage: 5 Hz to 500 Hz at 0.001 to 0.01 G ² /Hz
Shock	Operating: 40 G +/- 5% with pulse duration of 2 msec +/- 10% (equivalent to 51 cm/sec) Storage: 105 G +/- 5% with pulse duration of 2 msec +/- 10% (equivalent to 127 cm/sec)
Altitude	Operating: -50ft to 10,000 ft Storage: -50ft to 35,000ft
Supplied Accessories	USB Mouse, Regional Power Cord, 2 x mDP to DisplayPort cables, 8x Slimline DVD+/-RW Drive
Software Requirements	Control Center v15.3 will come pre-installed

Accessories

Accessories	Product Code
Workstation Monitor 24in 1080p 60Hz	110390
Workstation Keyboard (USB) - US International	110385
Workstation Keyboard (USB) – UK English	110384
Workstation Keyboard (USB) – Spanish	110383
Workstation Keyboard (USB) – Italian	110382
Workstation Keyboard (USB) – German	110381
Workstation Keyboard (USB) – French	110380
Workstation Keyboard (USB) – Arabic	110386