

Proguard and Plus T



- **Cost Effective Solution**
- **Traditional Design**
- **Simple to Install**
- **Timer Option**

Both Units Feature:

- Durable 3mm polycarbonate case
- Tamper protected against:
 - Cover removal
 - Cover screw removal (optional extra)
- Powerful piezo sounder provides up to 107dB(A) sound level at 1m
- High visibility xenon strobe giving excellent visual alarm signal
- Ultrabright comfort LED
- 2 year warranty

Plus T also features:

- SAB mode of operation
- Complete with 7.2V NiMH backup battery
- Fixed 20 minute cut-off timer

Flashguard Sounder products come with the following benefits:

- FREE Technical helpline
- Comprehensive logo design and screen printing service
- BS4737 compliant
- Compatible with any control panel
- Fully weather resistant to IP55
- Conformally coated electronics for complete protection against moisture
- Simple to install:
 - Fixing screw kit provided
 - Drilling template on carton



Proguard and Plus T Specification:

Sounder type:	Single piezo
Sounder output level @ 1m:	107dB(A)
Strobe frequency:	1Hz
Supply voltage:	10-15V
Current (Sounder):	300mA
Current (Strobe):	100mA
Current (Standby mode):	15mA
Battery (Plus T only):	7.2V 280mAh NiMH
Dimensions (H x W x T):	360mm x 190mm x 80mm

Decoy Units:

- Supplied with substantial moulded mounting brackets as standard
- Flashing LED module is available, providing a high intensity output from twin alternating LEDs, adding realism to a decoy unit (requires permanent 12V supply)

Colours Available:

Lenses	Lids
<input type="checkbox"/> Opal	<input type="checkbox"/> White
<input checked="" type="checkbox"/> Red	<input checked="" type="checkbox"/> Red
<input checked="" type="checkbox"/> Blue	<input checked="" type="checkbox"/> Blue
	<input checked="" type="checkbox"/> Yellow

