


Xpro









- For the Discerning Installer
- Large Area for Logos
- Wide Angle Lens
- Unique Styling
- High Reliability

Features:

- Durable 3mm polycarbonate case
- Enclosed electronics
- Two tamper protection devices:

Cover removal

Removal of unit from wall

- Piezo sounder provides up to 105dB(A) sound level at 1m
- High visiblity xenon strobe giving excellent visual alarm signal
- Dual flashing comfort LEDs
- Optional SCB mode of operation enables sounder to operate from internal battery power, allowing several units to be connected to a single control panel without risk of overloading the panel power supply
- Complete with 6V NiMH backup battery
- Selectable 9 or 15 minute cut-off timer to conform with noise abatement guidelines
- 2 year warranty

Flashguard Sounder products come with the following benefits:

- FREE Technical helpline
- Comprehensive logo design and screen printing service
- Fully BS4737 and BS EN50130-4 compliant
- · Compatible with any control panel
- Fully weather resistant to IP55
- · Conformally coated electronics for complete protection against moisture
- Simple to install:

5 second first fit test feature eliminates need to make more than one trip up the ladder

Fixing screw kit provided Drilling template on carton

Specification:

Sounder type: Single piezo (second piezo

available as optional extra)

Sounder output level @ 1m: 105dB(A)
Strobe frequency: 1Hz
Supply voltage: 10-15V
Current (Sounder): 300mA
Current (Strobe): 100mA
Current (Standby mode): 35mA

Battery: 6V 250mAH NiMH
Dimensions (H x W x T): 375mm x 225mm x 67mm

Decoy Units:

- Supplied with substantial moulded mounting brackets as standard
- Flashing LED module is available, providing a high intensity output from twin alternating LEDs, adding realism to a decoy unit (requires permanent 12V supply)



Klaxon Signals Ltd.

Wrigley Street, Oldham, Lancashire, OL4 1HW, UK.
Tel: +44 (0)161 287 5555 Fax: +44 (0)161 287 5511
E-mail: sales@klaxonsignals.com Web: www.klaxonsignals.com

