

# Xtravert







- Sleek Design
- High Performance & High Reliability
- Large Area for Logos
- Vertical Mounting

#### Features:

- Durable 3mm polycarbonate case
- Fully sealed and enclosed electronics
- Up to three protection devices:
  - Cover removal

Removal of unit from walll Cover screw removal (optional extra)

- Powerful piezo sounder provides up to 118dB(A) sound level at 1m
- High visibility xenon strobe giving excellent visual alarm signal
- Dual flashing comfort LEDs
- Optional SCB mode of operation enables sounder to operate from internal battery power, allowing several units to be connected to a single control panel without risk of overloading the panel power supply
- Adjustable sound option allows individual units to be identified in multiple unit installations
- Complete with 8.4V NiMH backup battery
- Selectable 9 or 15 minute cut-off timer to conform with noise abatement guidelines
- 3 year warranty

#### Flashguard Sounder products come with the following benefits:

- FREE Technical helpline
- Comprehensive logo design and screen printing service
- Fully BS4737 and BS EN50134-4 compliant
- Compatible with any control panel
- Fully weather resistant to IP55
- Conformally coated electronics for complete protection against moisture
  Cimple to instally
- Simple to install:
  - 5 second first fit test feature eliminates need to make more than one trip up the ladder
  - Fixing screw kit provided Drilling template on carton

#### **Specification:**

Sounder type:

Sounder output level @ 1m: Strobe frequency: Supply voltage: Current (Sounder): Current (Strobe): Current (Standby mode): Battery: Dimensions (H x W x T): Single piezo (second piezo available as optional extra) 118dB(A) 1Hz 10-15V 300mA 130mA 30mA 8.4V 320mAH NiMH 375mm x 225mm x 55mm

### **Decoy Units:**

- Supplied with substantial moulded mounting brackets as standard
- Flashing LED module is available, providing a high intensity output from twin alternating LEDs, adding realism to a decoy unit (requires permanent 12V supply)



## Klaxon Signals Ltd.

Wrigley Street, Oldham, Lancashire, OL4 1HW, UK. Tel: +44 (0)161 287 5555 Fax: +44 (0)161 287 5511 E-mail: sales@klaxonsignals.com Web: www.klaxonsignals.com

