



D/N 1080P AHD VR DOME IR Camera



Features

- Video Output: AHD 1080P / AHD 720P / Analog 1280H
- Video without compression, no delay with high quality and real-time monitoring.
- Long transmission distance–Coaxial cable (3C/5C): 300M / 500M, Twisted cable: 300M
- Seamless compatibility with the standard Analog equipment
- Automatically activates IR LED: Below 10Lux
- UTC function (AHD-Coaxial protocol)

Specifications

Model	AHD652A3.6
Resolution	1,920 (H) × 1,080 (V) @ 30 fps
Lens	3.6mm
Iris	F2.0

Angle of View	(H)72.2° (V)52.9° (D)94.3°
Max IR distance	20M
Infrared LED Angle	48°(H) x 30°(V)
Peak wavelength	850nm
System	NTSC or PAL
Image Sensor/Sensor type	1/2.9" CMOS Image Sensor
Effective pixels	1,984 (H) × 1,105 (V)
Scanning System	Progressive Scan
Menu Control	OSD Control
Sync. Mode/ Synchronization	Internal
IR cut filter	Auto Selectable, Automatic Switch from Color Mode to Monochrome
Min. illumination/Low Light Mode (Colour)	0.03 Lux / F1.8, 0 Lux (IR On)
S / N Ratio	More Than 55dB (AGC Off)
UTC	AHD-Coaxial protocol Supported
Auto Gain Control	Auto (16 Steps)
White Balance	ATW / AWC / INDOOR / OUTDOOR / MANUAL / AWB
Shutter Time	(Auto) 1/60(1/50)S - 1/50,000S (Manual) 1/30(1/25)S, 1/60(1/50)S, FLK, 1/240S, 1/480S, 1/1,000S, 1/2,000S, 1/5,000S, 1/10,000S, 1/50,000S
Sense Up	OFF / AUTO (X2 - X30)
2D WDR	OFF / AUTO (X2 - X30)
Back Light Compensation (BLC)	OFF / BLC / HSBLCL
3D Noise Reduction	2DNR & 3DNR
Defog	OFF / AUTO
Privacy Masking	OFF / ON
Privacy masking Zone	4 Zones
Languages	ENG / CHN1 / CHN2 / GER / FRA / ITA / SPA / POL / RUS / POR / NED / TUR / KOR / JPN / HEB / ARB
Video input / output	AHD1080P / AHD720P / 1280H
Operating temperature	- 40°C - + 50°C (-40°F - 122°F)

IP Rating	IP66
Vandal Resistant Rating / IK Rating	IK10
Dimensions	φ115(D) x 91mm(H)
Weight	370g
Power Supply	DC12V ±10%
Power Consumption	5.5W
