D/N 1080P AHD AF VR DOME IR Camera

Features

- Video Output: AHD 1080P / CVBS 1280H
- Video without compression, no delay with high quality and real-time monitoring.
- Long transmission distance–Coaxial cable (3C/5C): 300M / 500M, Twisted cable: 300M
- Seamless compatibility with the standard Analog equipment
- Automatically actives IR LED: Below 10Lux
- UTC function (AHD-Coaxial protocol)
- AF mode supported

Specifications

Model	AHD662AX2.8
Resolution	1,920 (H) × 1,080 (V) @ 30 fps
Lens	2.8 - 8mm

Iris	F1.6
Angle of View	(H) 95° - 47.2° (V) 68° - 35° (D) 127° - 59°
Infrared LED Angle	30°
Peak wavelength	850nm
System	NTSC or PAL
Image Sensor/Sensor type	1/2.9” CMOS Image Sensor
Effective pixels	1,984 (H) × 1,105 (V)
Scanning System	Progressive Scan
Menu Control	OSD Control
Sync. Mode/ Synchronization	Internal
IR cut filter	Auto Selectable, Automatic Switch from Color Mode to Monochrome
Min. illumination/Low Light Mode (Colour)	0.025 Lux / F1.6, 0 Lux (IR On)
S / N Ratio	More Than 55dB (AGC Off)
UTC	AHD-Coaxial protocol Supported
Auto Gain Control	Auto (16 Steps)
White Balance	ATW / AWC / INDOOR / OUTDOOR / MANUAL / AWB
Sense Up	OFF / AUTO (X2 ~ X30)
2D WDR	OFF / ON / AUTO
Back Light Compensation (BLC)	OFF / BLC / HSBLC
3D Noise Reduction	2DNR & 3DNR
Defog	OFF / AUTO
Privacy Masking	OFF / ON
Privacy masking Zone	4 Zones
AF mode	SEMI / AUTO / MANUAL
Languages	ENG / CHN1 / CHN2 / GER / FRA / ITA / SPA / POL / RUS / POR / NED / TUR / KOR / JPN / HEB / ARB
Video output	AHD 1080P / CVBS 1280H
Operating temperature	- 40°C - + 50°C (-40°F - 122°F)
IP Rating	IP66
Vandal Resistant Rating / IK Rating	IK10

Dimensions	φ140(D) x 102mm(H)
Weight	610g
Power Supply	DC12V ±10%
Power Consumption	7.7W