



8MP Day & Night Fixed IR Vandal Resistant Panoramic IP Camera



Features

- 8 megapixel CMOS image sensor
- Certified Immervision Enables (RPL code B5SST)
- H.265/HEVC and H.264/AVC high-performance video compression
- Simultaneous streaming of H.265 and H.264 encoded streams
- Smart H.264/H.265 supported
- 3D noise reduction (MCTF)
- 2D WDR function
- Digital PTZ supported
- IVS supported
- Tampering / Motion / Network lost detection event function
- SMART event
- High efficiency IR LED, radiant distance up to 20m
- Day & Night (IR cut removable)
- Built-in highly sensitive microphone
- 2-way audio supported
- Digital I/O : 1 in, 1 out
- ONVIF Profile S and Profile T supported
- Support Client Side Dewarping
- IP67 rain and dust resistant

Specifications

Model	F2R3682IM
Min. illumination/Low Light Mode (Colour)	Color : 0.04 Lux at F2.0 ; B/W : 0.009 Lux at F2.0
Focal Length	1.0mm
Iris	F2.8
Iris Control	Fixed IRIS
Angle of View	185° (H) 185° (V) 185° (D)
Peak wavelength	850nm
Beam Spread	90°
Max IR distance	20M
Pick Up Element	1/1.8" CMOS image sensor
Effective pixels	3864 (H) × 2180 (V) = 8,423,520 (Pixels)
CE	Yes, EMI CLASS B
FCC	Yes, EMI CLASS B
IP Rating	IP67
Vandal Resistant Rating / IK Rating	IK10
CPU	Intel® Core™ i7 or higher grade
OS	Windows 7 or above
RAM	8GB or above, Dedicated Graphics Card
Web browser	Microsoft® Internet Explorer® 9 or above
Audio Input / Output	Mono, 1.98 Vp-p , 2.2KΩ , Terminal Block
Audio	Two-way Audio, G.711 u-law / PCM / AAC, SIP, Built-in Microphone
Alarm Input / output	Digital 1 input (TTL, +3 – 5VDC) / 1 Output (MOS Relay contact N.O., Load.max. 40VDC,450mW/300mA,450mW), Terminal block
Video Compression	H.265/HEVC main profile, H.264 main and high profile , Motion JPEG

Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast 4 configurable streams in H.265 and H.264 and Motion JPEG, configurable frame rate and bandwidth
Number of streams	4
Video bitrate	128Kbps – 12Mbps; Frame rate and bit rate controllable on-the-fly; VBR / CBR / GOP supported, Fixed bitrate, Smart H.264/H.265
Encryption	Base64 HTTP encryption, HTTPS encryption, DDNS via HTTPS
Authentication	Digest HTTP authentication, RTSP authentication, TLS, 802.1x, DDNS via HTTPS
Address Filter	IP address filter, MAC address filter
Access	Multiple user access levels with password protection
User accounts	10 user accounts available
Multi IP address	Yes
Resolution	4.7M(2176 x 2160), 4M(2000 x 2000), 3M(1744 x 1744), 2M(1440 x 1440), 1M(1024 x 1024), 736 x 720, 480 x 480, 352 x 240
Maximum Frame Rate	up to 30 fps @ 2176 × 2160
Scanning System	Progressive Scan
Infrared Cut Filter	Auto / Day (Color) / Night (Mono) / Schedule
White Balance	ATW-NARROW / ATW-WIDE / AWC(MANUAL)
Back Light Compensation	Yes
Electrical Shutter	1/30(1/25)s – 1/30000s
Sense Up	Off / x2 / x4 / x8 / x16
Sense Up+	Yes
Auto Gain Control	60 dB Variable Gain
S / N Ratio	More than 50dB (AGC off)
3D Noise Reduction	Off / 1 – 32 Selectable
2D WDR	Off / Auto / x2 / x3 / x4 (by normal mode) Support Onvif

Privacy Masking	Off / On (4 zones)
Image Effects	Brightness, Contrast, Hue, Saturation, Sharpness
EV (Exposure Value)	Adjustable
Mobile Application	Integrated to LILIN mobile app (LILIN Viewer) iPhone, iPad, Android support
Video Management	ONVIF Profile S / ONVIF Profile T / IVS events, LILIN Navigator Enterprise 2.0 support, Third party VMS through LILIN HTTP API
SD Card (recording)	Support Micro SD/SDHC/SDXC card for circular recording (card is not included)
SD Card Compatible List	Micron - 32GB,64GB,128GB,256GB,512GB, 1TB (SDXC, U1, C10) 3Transcend - 34GB SD,8GB SDHC,32GB SDHC C10,128GB SDXC C10 3SanDisk - 38GB SDHC, 32GB, 64GB, 128GB SDHC C10 3Kingston - 364GB SDXC C10
Maintenance	Firmware update via HTTP and IP Scan; Firmware available at website
IVS Basic 1.0	Motion Detection, Tampering Detection, Advanced Motion Detection, Traffic Light Detection, Tripwire Detection, Object Counting
Alarm event triggers	Motion / Tamper / Audio / Alarm / Network lost detection / SmartEvent
Alarm event actions	FTP / SMTP / HTTP post / SD card / SAMBA / Alarm / SNMP Trap / Push Service notification
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
Ethernet	10/100 Mbps Base-T (Tx), RJ-45

ePTZ & Digital Zoom	Yes, ROI (Region of Interest)
OSD	Position configurable text overlay for date, time, camera ID, event status and watermark with customizable user demand data
CPU.Memory	Embedded SoC ARM Cortex-A9, 816MHz, 512MB DDR3L, 256MB flash memory
Network OS	Embedded Linux 3.10
Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, SIP, MQTT, QoS, SNMP V1/V2/V3, SNMP Trap and heart beat, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S , ONVIF Profile T, SDDP, Bonjour , 802.1x, SSL/TLS
Max number of online users	10 simultaneous users
Video Display	LILIN Universal ActiveX , LILIN Java Applet
Watermark	BMP logo
Log	Event & operation log & IVS event log
Schedule	Support holiday list
Network Storage	NAS (Support SAMBA/CIFS)
Starting Temperature	-10°C – +50°C (14°F – 122°F)
Operating temperature	-40°C – +50°C (-40°F – 122°F)
Storage temperature	-25°C – +60°C (-13°F – 140°F)
Operating humidity	0% – 90% RH
Power Supply	DC12V ±10% / PoE (IEEE 802.3af compliant)
Power Consumption	DC12V, 5.6W / PoE, 6.8W
Dimensions	Ø120 × 58.8 mm
Weight	485g
Casing Material	Aluminum alloy