



HD 30M IR Range Vari-focal Dome IP Camera



Features

- IR cut filter for day/night operations
- 30-meter infrared night vision
- 4MP resolution @ 20fps
- High Dynamic Range

Description

As with all M series cameras, MR2942X HD 30M-Range IR Varifocal Dome IP Camera in the M series features 4MP resolution at 20 frames per second, built-in Sense up+ technology to deliver stunning video in low-light conditions, and intelligent video surveillance (IVS) functions. Utilizing intelligent image signal processing, HDR, AGC control, and 3D Noise Reduction, the combination successfully delivers the ultimate low-light image without motion blur. The support of PoE, privacy mask, and white balance, as well as the minimum illumination of 0.21 Lux at F1.4 will satisfy multiple applications.

Specifications

Model	MR2942X
Image Sensor/Sensor type	1/3" CMOS image sensor
Effective pixels	2688(H) x 1520 (V) = 4,085,760 pixels
Video Compression	Smart H.264/ H.264 High/Main Profile, Motion JPEG
Resolution	4MP(2688 x 1520) , 1080p(1920 x 1080) , 1280x960(1280 x 960) , 720P(1280 x 720) , D1(720 x 480, 720 x 576) , VGA(640 x 480) , CIF(352 X 240)
Frame Rates	H.264 : up to 20 FPS @ 2688 x 1520, up to 30 FPS @ 1920 x1080 / MJPEG : up to 20 FPS @ 2688 x 1520, up to 30 FPS @ 1920 x1080
Lens	2.8 – 12mm
Iris	F1.4
Angle of View	(H)95°– 33° , (V)51°– 18° , (D)109°– 38°
Max IR distance	30m
Infrared LED Angle	60°, 90°
Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast 4 configurable streams in H.264 and Motion JPEG, configurable frame rate and bandwidth
Video bitrate	128Kbps – 12Mbps ; Frame rate and bit rate controllable on-the-fly ; VBR / CBR / GOP supported ; Fixed bitrate
Peak wavelength	850nm
Scanning System	Progressive scan
IR cut filter	Color (Day), Monochrome (Night), Auto, Schedule
Min. illumination/Low Light Mode (Colour)	0.21 Lux at F1.4 (Color) , 0.045 Lux at F1.4 (B/W) ; With Infrared LED 0 Lux
White Balance	Auto / Tungsten / Indoor / Fluorescents1 / Fluorescents2 / Outdoor1 / Outdoor2

Back Light Compensation (BLC)	On / Off
Shutter Time	1/30(1/25)s to 1/20000s
Sense Up	Off / 1 frame / 2 frames
Sense Up+	Yes
Auto Gain Control	36 dB variable gain
3D Noise Reduction	Off / 1 to 32 selectable
2D WDR	Off / Auto / x2 / x3 / x4 (by normal mode)
High Dynamic Range(HDR)	Up to 100dB (by HDR mode, 2 shutter line interleave)
Privacy Masking	Off / On (4 independent areas)
Other functions	Sharpness, Hue, Image flip, Image mirror
Lens distortion correction (LDC)	Yes
Live video	CVBS 1.0Vp-p, 75 ohm, connector
Encryption	Base64 HTTP encryption / Digest
Access	Multiple user access levels with password protection
User accounts	10 user accounts available
IP address filter	Yes
Multi IP address	Yes
Users	10 simultaneous users
OSD (On-Screen Display)	Text overly for date, time , and camera name
IVS (Intelligent Video Surveillance)	Advanced motion detection, Tripwire detection, Semaphore + Tripwire detection, Object counting
Alarm event triggers	Motion/Tamper/Network lost detection
Alarm event actions	FTP,SMTP, HTTP post, SD card, SAMBA
CPU	Embedded SoC ARM Cortex-A9, 600MHz, 256MB DDR3, 256MB flash memory
Firmware	Firmware upgrade via HTTP, and IP Scan
Network Interface/Ethernet	10Base-T / 100Base-TX, RJ-45
CE	Yes
FCC	Yes FCC EMI CLASS B
OS requirement	Windows 7, Windows 8, Windows 10
Web browser	Microsoft® Internet Explorer® 9.0 and later

CPU requirement	Intel i3 or above
RAM requirement	4GB or above, dedicated graphics card
Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, MQTT, QoS, SNMP, SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SDDP, Bonjour
Mobile phone	Integrated to LILIN mobile app (LILIN Viewer) iPhone, iPad, Android support
Video Management	ONVIF Profile S / LILIN Navigator Enterprise 1.0 and 2.0 / Third party VMS through LILIN HTTP API
Video Display	LILIN Universal ActiveX , LILIN Java Applet & HTML5
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
OS	Embedded Linux 3.10
SD Card (recording)	Support Micro SD/SDHC/SDXC (up to 128GB) card for circular recording (card is not included)
Operating temperature	-25°C – +50°C (-13°F – 122°F)
Dimensions	Ø120mm x 106mm
Weight	505g approx.
Power Supply	DC12V ±10% , Power over Ethernet (IEEE 802.3af compliant)
PoE	IEEE 802.3af
Power Consumption	DC12V, 5.4W / PoE, 7W