



Dimension Unit:mm

# PIH 252/254

- ⊕ Attractive Silver-Toned Finish
- ⊕ Sturdy Metal Housing for Maximum Camera Protection
- ⊕ Easy Lens Angle Adjustment
- ⊕ Special Circuit to Avoid Color Rolling



BLC



AGC



AWB



## Specifications

### ⊕ Dome Camera

Name	Metal Mini Dome Camera					
Series Number	PIH-252/254					
Type	Standard Resolution			Super High Resolution		
Model	NTSC	PIH-2522N6	PIH-2522N3.6	PIH-2542N6	PIH-2542N3.6	
	PAL	PIH-2522P6	PIH-2522P3.6	PIH-2542P6	PIH-2542P3.6	
Lens	Focal Length	6.0 mm	3.6 mm	6.0 mm	3.6 mm	
	Iris	F1.8	F2.0	F1.8	F2.0	
	Angle of View	H	44.5°	73°	44.5°	73°
		V	33.1°	54.5°	33.1°	54.5°
	D	56°	92°	56°	92°	
Power Supply	DC12V ± 10%					
Image Pick-up Device	Sony 1/3" Super HAD CCD Sensor					
Effective Pixels	NTSC	510 (H) x 492 (V)		768 (H) x 494 (V)		
	PAL	500 (H) x 582 (V)		752 (H) x 582 (V)		
Chip size	5.59mm(H) x 4.68mm(V)					
H/V Sync. Frequency	NTSC	15.734KHz / 59.94Hz				
	PAL	15.625KHz / 50Hz				
Scanning System	2:1 Interlace					
Sync. Mode	Internal					
Resolution	380TV Lines			540TV Lines		
Min. Illumination	0.2 Lux / F1.8			0.5 Lux / F1.8		
S/N Ratio	More than 50dB (AGC Off)					
Auto Gain Control	36dB Variable Gain					
White Balance	ATW					
Aperture Gain Correction	Horizontal , Vertical					
Electronic Shutter	1/60 (1/50) S ~ 1/100,000S (Auto)					
Back Light Compensation	Auto					
Video Output	CVBS 1.0Vp-p / 75 Ω BNC					
Gamma Characteristic	γ = 0.45					
Power Consumption	2.2W					
Operating Temperature	-10°C ~ + 50°C (14°F ~ 122°F)					
Dimension	Dome : Φ62.5 , Holder : Φ98					
Weight	310g					