

Analog dome camera

LTV-CCH-B7001-F3.6



- Electronic day-night dome camera
- 1/3" DIS
- 700 TVL
- 0.34 lux at F2.2
- f=3.6 mm lens
- AGC
- AWB
- BLC
- triaxis adjustment mechanism
- operating temp.: -40°C...60°C
- 12V (DC) 83mA
- Dimensions: 97.8x64.4mm

Video	Imaging device	1/3" DIS
	Effective Pixels (H×V)	976x496
	Electronic shutter speed	1/50 – 1/100 000sec.
	Resolution	700 TVL
	Video Min illumination	0.34 lux @ F2.2
	Video Output	1.0 Vp-p / 75 Ω composite
	Gamma Correction	0.45
	Synchronisation	Internal
	S-N Ratio	>62dB
Lens	Lens Type	Build-in, type M12
	Focal Length zoom ratio	f=3.6 mm, F2.2
	Angular Field of View (H)	68.44°
	iris Control	–
Functions	Day and Night	Auto(electrical) / Color / B/W
	IR illumination	–
	Backlight Compensation	BLC
	Gain control	AGC
	White Balance	AWB
	Digital Noise Reduction	–
	Sens-up frame integration	–
	Extended Dynamic Range	–
	Motion Detection	–
	Privacy Masking	–
	OSD menu	–
	Heater	–
Physical parameters	Input Voltage -Current	12B (DC) ± 10%, 83 mA
	Performance	Internal
	Ingress Protection	–
	Operating Temperature	-40°C...+60°C
	Dimensions L×D	97.8x64.4 mm
	Weight	0.3 kg.