

ECONOMY LINE

3 Mpix Outdoor Dome Camera

LTV CNE-831 48

Article No.: 22100034





Main Features:

- 3MP (2048 x 1536) resolution
- Day&Night (mechanical IR cut filter)
- varifocal lens f = 2,8 - 12 mm
- Supports P2P and IPv6
- H.264
- 12V DC / PoE
- IP66
- Mobile client support (Android/iOS)
- ONVIF Support



Accessories:

Picture	Article No.	Model Name
	42300024	LTV-BMW-JB4-E
	42300015	LTV-BMW-210-E

Video	
Image Sensor	1/3" CMOS
Effective Pixels	2048 x 1536
Electronic Shutter Speed	1/25 - 1/100000s
Min. Illumination	0 lux (IR LED ON)
Video Compression Format	H.264, MJPEG
Resolution	3MP (2048x1536), 1080P (1920x1080), 720P (1280x720), D1, CIF, 480x240
Multi-stream	3MP 2048x1536 (1~30fps) / 1920x1080 (1~30fps) / 1280x720 (1~30fps) / D1 (1~30fps) / CIF (1~30fps) / 480x240 (1~30fps)
Bitrate	64 Kbps~8 Mbps
Encoding	VBR / CBR
Lens	
Lens	Varifocal lens
Focal Length	2,8 - 12mm
FOV	2,8mm/79°- 12mm/17,00°
Function	
Video Output	CVBS Video Output (BNCx1)
Audio I/O	1 x Input, 1 x Output
IO	1 Alarm Input/ 1 Alarm Output
Day&Night	Auto (ICR), Color & B/W
IR Lights	20-30m
Backlight Compensation	Yes
Gain Control	Yes
White Balance	AWB / manual (default)
Motion Detection	Yes
WDR	Yes
Storage	Network/SD Card (max. 64GB)
ONVIF	ONVIF GB-T/28181-2011
CVBS/Video out	1 x BNC
Network	
Network	1 x RJ45
Protocols	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, IPv6
Miscellaneous	
Power Supply	12V DC, PoE
Power Consumption	< 4W / IR an < 5.5W
Protection Class	IP66
Operating Temperature	-20°C ... +50°C, 10% ... 90% Humidity
Dimensions	150 x 114 mm