

ECONOMY LINE

4 Mpix Dome Camera

LTV CNE-840 58

Article No.: 22700002





Main Features:

- 4 megapixel resolution (2688x1520)
- motor vario lens
- day/night (ICR)
- 3D DNR, Digital WDR
- CVBS video output and two-way audio
- H.265 video compression
- PoE
- remote access via apps



Accessories:

Picture	Article No.	Model
	42300024	LTV-BMW-JB4-E
	42300015	LTV-BMW-210-E

Camera	
Image Sensor	1/3" CMOS
Effective Pixels (HxV)	2688 x 1520
Electronic Shutter Speed	1/25s ~ 1/100000s
Min. Illumination	Color: 0.05 Lux @F1.2, AGC on; B/W: 0.01 Lux @ F1.2, AGC on
Lens	
Focal Length	2.8 - 12 mm (F=1.4)
Lens	Motor vario lens
FOV	84° - 35°
Video	
Compression	H.265 / H.264 / MJPEG
Resolution	4MP (2688x1520), 2K (2560x1440), 3MP (2304x1296), 720P (1280x720), D1, CIF, 480x240
Framerate	Main Stream 60Hz: 4MP (1~15fps) / 2K (1~25fps) / 1080P (1~30fps) / 720P (1~30fps) 50Hz: 4MP (1~12fps) / 2K (1~25fps) / 3MP (1~25fps) / 1080P (1~25fps) / 720P (1~25fps)
Bitrate	64 Kbps ~ 8 Mbps
Function	
IR Lights	30 m
Day/Night	ICR
Audio	1x Mic In, 1x Mic Out
Video Output	CVBS Video Output (1x BNC)
Alarm I/O	1x CH Input / 1x CH Output
Micro SD	Max. 64 GB
PTZ	1x RS485
Network	
Network	RJ45
Protocols	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Web Viewer	Internet Explorer
Miscellaneous	
Power Supply	DC 12V / PoE
Power Consumption	<3,5W
Operating Temperature	-20°C ... +50°C, 10% ~ 90% humidity
Protection Class	IP66, IK10
Dimensions	Ø 150 x 114 mm
Weight	1.08 kg