

ECONOMY LINE

5 Mpix Dome Camera

LTV CNE-850 48

Article No.: 22700005





Main Features:

- 5 Megapixel resolution (2592x1944)
- Day/Night (ICR)
- IR illumination up to 30 m
- 3D DNR, Digital WDR
- CVBS video output and two-way audio
- H.265 video compression
- Gigabit ethernet network port
- PoE
- remote access via apps



Accessories:

Picture	Article No.	Model
	42300010	LTV-BMW-200-E5
	42300011	LTV-BMW-P20-E5

Camera	
Image Sensor	1/1.8" CMOS
Effective Pixels (HxV)	2592x1944
Electronic Shutter Speed	1/25s ~ 1/100000s
Min. Illumination	Color: 0.01 Lux @F1.2, AGC on; B/W: 0.001 Lux @ F1.2, AGC on
Lens	
Focal Length	3.6 - 10 mm (F=1,4)
Lens	Varifocal lens
FOV	83.7° - 36.7°
Video	
Compression	H.265 (Main Profile @Level4.1 High Tier) / H.264 / MJPEG
Resolution	5MP (2592x1944), 2K (2560x1440), 1080P (1920x1080), 720P (1280x720), D1, CIF, 480x240
Framerate	Main Stream 60Hz: 5MP (1~30fps) / 2K (1~30fps) / 1080P (1~30fps) / 720P (1~30fps) 50Hz: 5MP (1~25fps) / 2K (1~25fps) / 1080P (1~25fps) / 720P (1~25fps)
Bitrate	64 Kbps ~ 10 Mbps
Function	
IR Lights	30 m
Day & Night	ICR
Backlight Compensation	Digital WDR
Noise Reduction	2D / 3D DNR
Audio	1x Mic In, 1x Mic Out
Compression	G.711A / U
Video Output	CVBS Video Output (1x BNC)
Alarm I/O	1x CH Input / 1x CH Output
Micro SD	Max. 64 GB
PTZ	1x RS485
Network	
Network	1x RJ45 Gigabit ethernet network port, 10M/100M/1000M self adaptive
Protocols	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Compatibility	ONVIF, GB-T / 28181-2011
Web Viewer	Internet Explorer
Miscellaneous	
Power Supply	DC 12V / PoE
Power Consumption	<3W
Operating Temperature	-20°C ... +50°C, 10 % ~ 90 % humidity
Protection Class	IP66
Dimensions	Ø 161 x 137.3 mm
Weight	1.5 kg