

## 4-Channel Triplex DVR with 1TB HDD incl.

LTV-DVR-0432-HV



- 4-channel triplex DVR
- 1 audio input
- H.264
- resolution and recording speed:  
main stream - CIF, 2CIF: 25 fps, 4CIF/960H 12 fps  
second stream: CIF/QCIF: 25 fps/ channel
- 2 monitor outputs (HDMI+VGA)
- 1TB HDD incl.
- 2 USB
- IR remote
- motion detector
- RS-485
- Ethernet
- Power supply 12V (DC)

Video/audio input	Video input	4xBNC (1.0Vp-p, 75Ω) PAL/NTSC
	Audio input	1xRCA (2.0Vp-p, 1kΩ)
	Two-way audio input	1xRCA (2.0Vp-p, 1kΩ)
Video/audio output	BNC output	1xBNC (1.0 Vp-p, 75 Ω)
	BNC resolution	PAL: 704x576; NTSC: 704x480
	HDMI/VGA output	1 HDMI & 1 VGA
	HDMI/VGA resolution	1920×1080P / 60 Hz, 1600×1200 / 60 Hz, 1280×1024 / 60 Hz, 1280×720 / 60 Hz, 1024×768 / 60 Hz
	Loop output	-
	Audio output	1xRCA (2.0Vp-p, 1KΩ)
Recording	Video compression	H.264
	Audio compression	G.711
	Stream type	Video / Video end audio
	Frame rate	WD1: 12 fps; 4CIF: 12 fps; 2CIF: 25 fps; CIF: 25 fps
	Video bit rate	32...3072Kbps / or user defined, max 3072 Kbps
	Audio bit rate	64 Kbps
	Dual stream	Support; Sub-stream: CIF, QCIF 25 fps
	Synchronous playback	4 ch
HDD	SATA	1xSATA
	Capacity	Up to 4TB capacity
Interface	Network	1xRJ45 10M / 100M
	Serial interface	1 RS-485
	USB	2xUSB 2.0
	Alarm input	-
	Alarm output	-
Network	Ethernet	10BASE-T, 100BASE-TX, RJ45
	Protocol	QoS Layer 3 DiffServ, TCP/IP, UDP/IP, HTTP, RTSP, RTP/UDP, RTP/TCP, mDNS, UPnP™, SMTP, DHCP, DNS, DynDNS, NTP, SNMPv1/v2c/v3(MIB-II), IGMP, ICMP, SSLv2/v3, TLSv1
	Web Viewer	Internet Explorer 7.0 or later, Firefox, Chrome, PDA/Smartphones
	Security	Multi-level access with password protection
General	Input voltage	12V (DC)
	Consumption	≤10W
	Operating Temperature	-10°C...+55°C
	Operating Humidity	10...90%
	Box	1U
	Dimension (W x D x H)	315×230×45 mm
Weight (With hard disks)	≤2 kg	