

HD-SDI Cameras

LTV-HSDNO20-M2

Full HD-SDI Outdoor PTZ Dome Camera



Key Features:

- 1/2.8" Progressive Scan CMOS
- 20X optical zoom, 16X digital zoom
- 1.485Gbps SDI interface
- True Day/Night, D WDR, 3D DNR
- 3D intelligent positioning
- Outdoor / Indoor
- IP66 Casing



| | | |
|------------------------|----------------------|--|
| Camera | Imaging Device | 1/2.8" Progressive Scan CMOS |
| | Signal System | PAL/NTSC |
| | Max. Resolution | 1920(H)*1080(V) |
| | Min. Illumination | 0.03 Lux @(F1.6,AGC ON) |
| | Shutter Time | 1/1s to 1/30,000 s |
| | Lens | Zoom-lense with Auto-Focus F=4.7~94mm |
| | Lens Mount | M12 |
| | Adjustment Range | Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360° |
| | Audio Input | 1-ch Mic/Line Input 2-2.4V 1 kΩ ± 10% |
| | Audio Output | 1-ch impedance 600 Ω |
| | Day & Night | IR cut filter with auto switch |
| | Max. Frame Rate | N/A |
| | HD Video Output | SMPTE292M (HD-SDI) |
| | Synchronization | Internal |
| | Video Output | 1Vp-p Composite Output (75Ω/BNC) |
| S/N Ratio | >50dB | |
| Backlight Compensation | BLC | |
| Alarm Input / Output | 7 / 2 | |
| Menu | D/N Mode | Color/ BW/ EXT |
| | Auto White Balance | ATW/ AWC-SET / Indoor / Outdoor / Manual / Fluorescent Lamps |
| | Private Mask | 24 programmable zones |
| | Motion Detection | supported |
| | Heating Unit | Built-in |
| | Gain Control | AGC |
| | Language | English/ Japanese/ CHN1/ CHN2/ Korean/ German/ French/ Italian/ Spanish/ Polish/ Russian/ Portuguese/ Dutch/ Turkish/ Hebrew/ Arabic |
| | Function | Digital noise reduction (2d-DNR + 3D-DNR), D-WDR, Motion Detection, Privacy Masking, PTZ, BLC, AGC |
| General | Operating Conditions | -50 °C...+65 °C Humidity 90% or less (non-condensing) |
| | Power Supply | 24 V AC ± 10% |
| | Power Consumption | Max. 40W |
| | Weather Proof | IP66 |
| | Dimension | 220 x 325.5 mm |
| | Weight | 5 kg |