

## Full HD 1080p (2Mpix) Box Camera

LTV-ICDM1-E4230



- 1/2.9" Progressive Scan CMOS
- Max. Full HD 1080p (1920x1080) resolution
- Day & Night(ICR)
- H.264
- Alarm I/O
- SD Memory slot
- 12V (DC) & PoE

Video	Imaging Device	1/3" CMOS
	Effective Pixels (H/V)	1280×960
	Electronic shutter speed	1/25...1/100000 c
	Resolution	1280×960
	Max. framerate	Max. 25fps at all resolutions
	Min. illumination	0.1 lk (color), at F=1.2
	Video compression format	H.264
Lens	Mount Type	without lens, CS/C
	Focal Length	-
	Iris control	DC
Video output (for installation)	Video output	CVBS : 1.0 Vp-p / 75 Ω Composite, 704 x 480(N), 704 x 576(P)
	Scanning Frequency	CVBS : 1.0 Vp-p / 75 Ω composite, 704 x 480(N), 704 x 576(P)
Audio	Audio I/O	Line in/ Line out
	Audio Compression Format	G.711A
Operational	Day & Night	Auto (ICR), Color & B/W.
	IR LED	-
	Backlight Compensation	BLC
	Gain Control	AGC
	White Balance	AWB / Manual (presets)
	Sens-up	-
	Motion detection	Yes
	Alarm I/O	Input 1 / Output 1
Network	Memory Slot	Micro SD;SD; max. 64GB
	Ethernet	RJ45
	Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	Web Viewer	Internet Explorer
Mechanical & Electrical & Environmental	Security	HTTPS, login authentication, IP address filtering
	Input Voltage-Current	12V (DC), 4.3W; PoE (IEEE 802.3af), 4.3W.
	Operating conditions	Indoor
	Operating Temperature	-10°...+50°C
	Dimensions (WxHxD)	70×60×145
Weight	0.4 kg	