

## SMART LINE

### 1 MPix Indoor Dome Camera

LTV-ICDM1-SD7230-F3.6



#### • Main Features:

- H.264 & MJPEG dual-stream encoding
- Max. 25/30fps@720P (1280 x 720)
- DWDR, Day/Night (ICR), 3DNR, AEB, AGC, BLC
- 3.6mm fixed lens
- Max. IR LEDs Length 20m
- DC 12V
- PoE



Camera		
Image Sensor	1/4" 1 Megapixel progressive scan CMOS	
Pixels	1280 (H) x 720 (V)	
Electronic Shutter Speed	Auto/Manual 1/3(4) ~ 1/10000	
Min. Illumination	Color: 0.01Lux/F1.2; 0Lux (IR on)	
S/N Ratio	More than 50dB	
Lens		
Focal Length	3.6mm (2.8mm, 6mm optional)	
Lens Type	Fixed Lens	
FOV	54,9°	
Video		
Compression	H.264/MJPEG	
Resolution	720P (1280 x 720)	
Frame Rate	Main Stream	720P (1 ~ 25/30fps)
	Sub Stream	D1/CIF (1 ~ 25/30fps)
Bit Rate	H.264: 56K ~ 8192Kbps	
Camera Features		
Day/Night	Auto(Electronic) / Color / B/W	
Backlight Compensation	BLC / HLC / DWDR	
White Balance	Auto	
Gain Control	Auto/Manual	
Noise Reduction	3D	
Privacy Masking	Up to 4 areas	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Protocol	IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	
Compatibility	ONVIF, PSIA, CGI	
Smart Phone	iPhone, iPad, Android	
Miscellaneous		
Power Supply	DC 12V, PoE (802.3af)	
Power Consumption	<2W	
Working Environment	-30°C ... +60°C, Less than 95%RH	
Dimensions	110 x 54mm	
Weight	0,25kg	