

SMART LINE

Full HD Outdoor Mini PTZ Dome Camera

LTV-ISDNI3-SDM2



- **Main Features:**
- 3,0mm ~ 9,0mm (3x) optical zoom
- Max. 240°/s pan speed, 0° ~ 360° endless pan rotation
- Micro SD memory
- IP66, IK10
- PoE



Camera		
Image Sensor	1/2,8" Exmor CMOS	
Pixels	1920 (H) x 1080 (V), 2 Megapixel	
Electronic Shutter Speed	1/1 - 1/30,000s	
Min. Illumination	Color: 0.05Lux@F1.6, B7W: 0,005Lux@F1.6	
S/N Ratio	More than 50dB	
Lens		
Focal Length	3,0mm ~ 9,0mm (3x Optical Zoom)	
Focus Control	Auto/Manual	
FOV	3 mm = 82,4°; 9 mm = 32,5°	
Video		
Compression	H.264/MJPEG	
Resolution	1080P (1920 x 1080) / 720P (1280 x 720)	
Frame Rate	Main Stream	1080P/D1 (1 ~ 25/30fps), 720P (1 ~ 50/60fps)
	Sub Stream	D1/CIF (1 ~ 25/30fps)
Bit Rate	H.264H: 56K ~ 8192Kbps, MJPEG: 56K ~ 20480Kbps	
Audio		
Compression	G.711a / G.711u (32kbps) / PCM (128kbps)	
Interface	1/1 channel In/Out	
Camera Features		
Day/Night	Auto(ICR) / Color / B/W	
Backlight Compensation	BLC / HLC / DWDR	
White Balance	Auto, ATW, Indoor, Outdoor, Manual	
Gain Control	Auto/Manual	
Noise Reduction	2D / 3D	
Privacy Masking	Up to 24 areas	
Digital Zoom	16x	
PTZ		
Pan/Tilt Range	Pan: 0° ~ 360° endless; Tilt: 0° ~ 90°, auto flip 180°	
Manual Control Speed	Pan: 0,1° ~ 240°/s; Tilt: 0,1° ~ 160°/s	
Preset Speed	Pan: 240°/s; Tilt: 160°/s	
Preset	80(DH-SD), 255(Pelco-P/D)	
PTZ Mode	5 Pattern, 8 Tour, 5 Auto Scan, Auto Pan	
Speed Setup	Human-oriented focal length/speed adaption	
Power up Action	Auto restore to previous PTZ and lens status after power failure	
Idle Motion	Activate Present/Pan/Scan/Tour/Pattern if there is no command in the specified period	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Protocol	IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour	
Compatibility	ONVIF Profil S	
Smart Phone	iPhone, iPad, Android	
Auxiliary Interface		
Memory Slot	Micro SD, Max 64GB	
Miscellaneous		
Power Supply	DC 12V, PoE (802.3af)	
Power Consumption	10W	
Working Environment	-20°C ... +60°C, Less than 90%RH	
Ingress Protection	IP66	
Dimensions	160 x 132mm	
Weight	1,33kg	