

## Full HD 1080p (2Mpix) outdoor speed PTZ dome camera

LTV-ISDNO20W-AM2



- Optical 20X, Digital 8X Selectable
- Full Frame at HD1080p, Two way Audio
- Video Compression: H.264, MJPEG (Dual Stream)
- Day & Night (IR Cut Filter), DSS
- ONVIF Support
- Embedded Intelligent Video Analytics
- Burnt-in Text, Video Motion Detection Support
- Comprehensive SDK Support
- Stealth Spin® (World Most Silent Speed Dome)
- 0.1° Dome System Accuracy
- Controlling Pan/Tilt Speed While Zooming

Video Content Analysis (included as Standard)	
High Performance	Advanced tracking algorithm and low false alarm rate
Easy to Use	Intuitive web browser interface
Detection Zones and Rules	Up to 40 zones (multi-segment, polygons and lines) 60 VCA filter in total
On-screen Display	Real-time display of tracking data and events via activeX plug-in in IE browse
Burn in Annotation	Allows the VCA annotation to be burnt in to the raw video stream for displaying on third party application
Tamper Detection	Recognize camera tampering via VCA detect
Video Content Analysis (Option extension license)	
Available License	VCAcountIP, VCAaccessIP, VCAsurveillanceIP, VCAadvancedIP
VCA Detection Filters	Enter, Exit, Appear, Disappear, Stop, Direction, Dwell, Speed, Tailgating, Object Classification
VCA Features	- Up to 20 Onscreen Counter Displays - CountingLine for accuracy people and vehicle counting, - VCA Event Metadata Streaming (RTSP/RTP), - VCA calibration for right object size detection

Video	Imaging device	1/3" Progressive scan CMOS
	Effective pixels	1/1 to 1/10 000 s
	Electronic shutter speed	1920x1080
	Resolution	Max. 30fps at all resolutions
	Max. frame rate	Color: 1.5 Lux (50 IRE) / 0.02Lux(Sens-up); B/W: 0.1 Lux (50 IRE) / 0.001Lux(Sens-up)
	Min. illumination	>50dB
	Video compression format	H.264, MJPEG
	S/N Ratio	Focal Length zoom Ratio x20 with autofocus
Lens	Lens type	f=4.45-89.0 mm, F1.6-2.9
	Focal length	20x
	Auto iris	8x
Video output (for installation)	Video output	Analog video output for installation only
Audio	Audio I/O	Line in/ Line out
	Audio Compression Format	G.711A
Operational	Day & Night	Auto (ICR), Color & B/W.
	Gain Control	AGC
	White Balance	Auto / Manual
	Wide Dynamic Range	WDR
	Motion detection	Yes
	Alarm I/O	4 Input / 2 Output
	Memory Slot	Micro SD
	Heater	Yes
PTZ	Pan Range	360° without restriction
	Tilt Range	5°-185°
Network	Ethernet	10/100BASE-T
	Protocol	TCP/IP, UDP/IP, HTTP, RTSP, RTCP, RTP/UDP, RTP/TCP, SNTP, DHCP, DDNS, SSL v2/v3, IEEE 802.1X, SNMPv2/v3
	Web Viewer	Internet Explorer
Miscellaneous	Security	Multi-level access with password protection
	Input Voltage-Current	24 VAC 60/50Hz PoE+ (802.3at)
	Operating conditions	Outdoor
	Ingress Protection	IP66
	Operating Temperature	AC24V: -40 °C – 50 °C; PoE: -10 °C – 50 °C
	Dimensions (LxH)	248 x 300 mm
Weight	4,6 kg	

\*If VCA is activate, frame rate is limit to max15fps@1080p. Limitations are based on V.1.6.0 firmware release and could be changed without notice