

## HD-SDI Displays

LTV-MCL-2213SDI

### 22" HD-SDI Display



#### Key Features:

- 22" Premium HD-SDI LED Monitor
- Resolution 1920 x 1080
- De-Interlace and Noise Reduction
- Inputs: HD-SDI, HDMI, VGA, RCA, BNC
- Outputs: HD-SDI, BNC



General	Diagonal size	22"
	Aspect ratio	16:9
	Number of pixels	1920 x 1080
	Color depth	16.7 Million
	Backlight	LED
Optical	Brightness	300 cd/m <sup>2</sup>
	Contrast ratio	10000:1
	Response time (Tr + Tf)	5 ms
	Viewing angle	Vertical -80°~80°    Horizontal -85°~85°
Operation	Input Interface	BNC x 1, VGA x 1, HDMI x 1, RCA x 2, PC Audio x 1, SDI x 1
	Output Interface	BNC x 1, SDI x 1
	Looped Inputs	BNC x 2
	OSD	Picture Mode, Contrast, Brightness, Color, Tint, Sharpness, Color Temp, DNR
	OSD Languages	English, German, French, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech
	Speaker	1.5 W x 2
	Remote control	supported
Video	Signal System	PAL / NTSC
	Video Processing	Motion Adaptive 3D De-Interlace and DNR, 4H Comb filter Y/C separation
Electrical	Power Supply	AC 100-240V 50/60HZ
	Power Consumption	30 W
Mechanical	Case Material	Plastic
	Dimension (W x H x D)	524 x 375 x 170 mm
	Working Temperature	0°C ...+40°C
	Mounting interface	100 x 100 mm VESA-Mount
	Net weight (Monitor & stand)	5.3 Kgs
	Delivery set	Monitor, Power cord with adapter, VGA cable, User Manual, Fernbedienung