




## 8000 SERIES HYBRID NVRs AT-A-GLANCE







	32 CHANNELS		
			
<b>Model Number</b>	8732 R	8532 R	8532 S
<b>Base Part Number</b>	28065	28066	28067
<b>Total Inputs</b>	32		
<b>Analog/IP Inputs</b>	16/32		
<b>PoE Ports</b>	0		
<b>Channel Licenses Included</b>	32		
<b>Analog Performance</b>	480 FPS @ 4CIF	240 FPS @ 4CIF	
<b>IP Performance (primary plus alternate stream)</b>	80 Mbps		
<b>Analog Compression</b>	H.264		
<b>Local Area Network</b>	GigE		
<b>Camera Network</b>	GigE		
<b>Analog Resolutions</b>	4CIF/2CIF/CIF		
<b>IP Resolution</b>	Camera dependent		
<b>Operating System</b>	Embedded Linux		
<b>Alarms</b>	8 In / 4 Out		
<b>Audio</b>	4 In / 2 Out		
<b>Local Control</b>	Yes (IP Camera Capable)		
<b>Video Out</b>	HDMI/Composite		
<b>Max HDDs</b>	4		
<b>Max HD Storage</b>	Up to 24 TB		
<b>Storage Redundancy</b>	Mirroring (reduces throughput)		
<b>Data Ports</b>	4 USB, 1 RS-232, 1 RS-485		
<b>Docking Station</b>	Yes		No
<b>Dimensions (H x W x D)</b>	3.1 x 17.4 x 16.0 in (8.0 x 44.2 x 40.6 cm)		3.2 x 16.9 x 16.0 in (8.1 x 43.0 x 40.6 cm)
<b>Environmental</b>	41° to 105° F (5° to 40° C)		
<b>Power Supply</b>	Internal 115/230 VAC (auto-sensing); 75 W max		
<b>Weight (add 5.5 lbs/2.5 Kg for docking station)</b>	18.5 lbs (8.4 Kg)		13 lbs (5.9 Kg)
<b>Battery Backup</b>	Yes		
<b>Mounting Options</b>	Dock, Desk, Wall	Dock, Desk, Wall	Desk, Wall
<b>Front Panel QR Code*</b>	Yes		
<b>Analytics</b>	Included: Motion Detection / Optional: Camera Obstruction Detection, Field of View Change, Trip Wire, Loitering, Presence Detection		

\*The QR Code on the front panel contains useful information about the recorder, such as model number and serial number. When the code is scanned using the March Networks GURU smartphone application, this information allows integrators to easily check warranty status, initiate an express RMA, get in-field diagnostics support, review and change recorder IP addresses, register/unregister from the Enterprise Service Manager, and go through SSH to view storage information.

### 2-year Advance Replacement plan on all Recorders:

- Options for Repair & Return or Advance Replacement
- March Networks incurs all shipping costs—both ways—for AR's
- All NVR components are covered, including HDDs

## 8000 SERIES HYBRID NVRS AT-A-GLANCE

	16 CHANNELS			8 CHANNELS		4 CHANNELS
						
<b>Model Number</b>	8716 P	8516 R	8516 S	8708 S	8508 S	8704 S
<b>Base Part Number</b>	34246	28646	28068	28570	28568	28569
<b>Total Inputs</b>	16			8		4
<b>Analog/IP Inputs</b>	8/16	16/16		8/8		4/4
<b>PoE Ports</b>	8	0		0		0
<b>Channel Licenses Included</b>	16			8		4
<b>Analog Performance</b>	30 FPS @4CIF	240 FPS @ 4CIF		240 FPS @ 4CIF	120 FPS @ 4CIF	120 FPS @ 4CIF
<b>IP Performance (primary plus alternate stream)</b>	80 Mbps			80 Mbps		80 Mbps
<b>Analog Compression</b>	H.264			H.264		H.264
<b>Local Area Network</b>	GigE			GigE		GigE
<b>Camera Network</b>	10/100 Base-T	GigE		GigE		GigE
<b>Analog Resolutions</b>	4CIF/2CIF/CIF			4CIF/2CIF/CIF		4CIF/2CIF/CIF
<b>IP Resolution</b>	Camera dependent			Camera dependent		Camera dependent
<b>Operating System</b>	Embedded Linux			Embedded Linux		Embedded Linux
<b>Alarms</b>	2 In / 1 Out	8 In / 4 Out		2 In / 1 Out		2 In / 1 Out
<b>Audio</b>	2 In / 1 Out	4 In / 2 Out		2 In / 1 Out		2 In / 1 Out
<b>Local Control</b>	Yes (IP Camera Capable)			Yes (IP Camera Capable)		No
<b>Video Out</b>	HDMI/Composite			HDMI/Composite		No
<b>Max HDDs</b>	2	4		2		2
<b>Max HD Storage</b>	Up to 16 TB	Up to 24 TB		Up to 16 TB		Up to 10 TB
<b>Storage Redundancy</b>	Mirroring (reduces throughput)			Mirroring (reduces throughput)		Mirroring (reduces throughput)
<b>Data Ports</b>	4 USB, 1 RS-232	4 USB, 1 RS-232, 1 RS-485		4 USB, 1 RS-232		2 USB, 1 RS-232
<b>Docking Station</b>	No	Yes	No	No		No
<b>Dimensions (H x W x D)</b>	3.6 x 11.3 x 12.0 in (9.18 x 28.7 x 30.6 cm)	3.1 x 17.4 x 16.0 in (8.0 x 44.2 x 40.6 cm)	3.2 x 16.9 x 16.0 in (8.1 x 43.0 x 40.6 cm)	3.6 x 11.3 x 12.0 in (9.18 x 28.7 x 30.6 cm)		3.2 x 8.3 x 5.0 in (8.1 x 21.2 x 12.6 cm)
<b>Environmental</b>	41° to 105° F (5° to 40° C)			41° to 105° F (5° to 40° C)		41° to 105° F (5° to 40° C)
<b>Power Supply</b>	External 110/220 VAC (auto-sensing); 60 W max	Internal 115/230 VAC (auto-sensing); 75 W max		External 110/220 VAC (auto-sensing); 60 W max		External 110/220 VAC (auto-sensing); 20 W max
<b>Weight (add 5.5 lbs/ 2.5 Kg for docking station)</b>	7.8 lbs (3.6 Kg)	18.5 lbs (8.4 Kg)	13 lbs (5.9 Kg)	7.3 lbs (3.3 Kg)		3.3 lbs (1.5 Kg)
<b>Battery Backup</b>	Yes			Yes		Yes
<b>Mounting Options</b>	Desk, Wall	Dock, Desk, Wall	Desk, Wall	Desk, Wall		Desk, Wall
<b>Front Panel QR Code*</b>	Yes			Yes		Yes
<b>Analytics</b>	Included: Motion Detection / Optional: Camera Obstruction Detection, Field of View Change, Trip Wire, Loitering, Presence Detection					

\*The QR Code on the front panel contains useful information about the recorder, such as model number and serial number. When the code is scanned using the March Networks GURU smartphone application, this information allows integrators to easily check warranty status, initiate an express RMA, get in-field diagnostics support, review and change recorder IP addresses, register/unregister from the Enterprise Service Manager, and go through SSH to view storage information.

North America . . . . . 1 800 563 5564  
 Latin America . . . . . +5255 5259 9511  
 Europe . . . . . +39 0362 17935  
 Asia . . . . . +65 6818 0963  
 Australia and New Zealand . . . +61 1300 089 419  
 Middle East and Africa . . . . . +971 4 399 5525

© 2017, March Networks, An Infinova Company. All rights reserved. Information in this document is subject to change without notice. MARCH NETWORKS, March Networks Command, March Networks Searchlight, March Networks RideSafe, and the MARCH NETWORKS logo are trademarks of March Networks Corporation. Infinova is a trademark of Infinova Corporation. All other trademarks are the property of their respective owners. 060-3172-00-F  
[marchnetworks.com](http://marchnetworks.com)

