

NDR891

Full HD 1080p, Fixed Outdoor IR Dome Network Camera

1/2.7" 2MP Lumii sensor, 1080p, H.264/MJPEG/MPEG4 triple streaming, Tamron lens, 25M IR mechanical day/night, intelligent detection, PoE, ePTZ, micro SD/SDHC card slot, vandal-proof



The NDR891 is a high definition, day/night camera incorporating a 25M IR illuminator to show maximum detail in even the most extreme environments. Its uniform light intensity feature ensures objects can be captured in full detail without flares. H.264/MJPEG/MPEG4 triple streaming provides more flexible video encoding selections. As part of MESSOA Smart IP products family, the NDR891 features intelligent detection capabilities including motion, audio, blur and network disconnection detection. It also supports local storage to micro SD/SDHC card to ensure nothing is missed in case the network goes down. Vari-focal, 3-axis and PoE features facilitate simple installation. Along with a water and vandal proof housing, the NDR891 is guaranteed to keep working no matter the conditions.

Features



■ Lumii™ II Technology

Our Lumii™ technology delivers high sensitivity images without blur. Lumii™ helps increase the sensitivity and reduces video noise in low light conditions. Night images become bright and clear.

■ Full HD 1080p Image

Clear and detailed full HD quality images in all conditions. Unlike traditional megapixel cameras, full HD offers higher resolutions and better frame rates at an international industry standard. Blurry images are reduced and individuals and objects of interest come through in perfect clarity.

■ Cost-saving H.264 Support

The NDR891 supports the H.264 compression standard. H.264 greatly reduces the size of video compared to MJPEG and MPEG4 without compromising image quality. Storage and bandwidth needs are reduced. Plus, H.264 is expected to become the video standard of choice, so your camera is future proofed.

■ PoE Facilitates Easy Installation

Built in support for Power Over Ethernet reduces cost and adds flexibility to the camera. A single cable connection is used to view, power, and control the camera. Installation cost are reduced since there is no need for separate cables.

■ ONVIF Compliant

ONVIF is an open industry forum for the development of a global standard for the interface of network video products. The NDR891 supports ONVIF thus allowing interoperability between network video products regardless of brand.

■ Versatile Detection Capabilities

The NDR891 has a variety of intelligent detection functions, including motion, audio, blur and network disconnection detection. Event-specific monitoring enables you to receive alerts upon event and saves storage cost by only recording when a specific event happens.

■ Uniform Light Intensity

The NDR891's IR LEDs produce smooth even light distribution across the seeing range as far as 25 meters (82 feet) away. Each part of a picture has uniformly high resolution and contrast from the center to the edges of the field. The full-field capture ensures you don't miss any detail.

■ Continuous No-Interruption Recording

Record JPEG images or video clips for several days with the built in micro SD/SDHC card slot for up to 32 GB. Keep recording and prevent data loss even when the network goes down. Moreover, the camera's built-in FTP server enables users to view the saved files conveniently from a remote site.

■ Completely Vandal-Proof

A vandal-proof bubble and IK-10 rated impact-resistant housing protect the camera against extreme weather and vandalism, making it perfect for outdoor surveillance.

■ Climate Protection

An optional heater maximizes protection of surveillance equipment in extremely cold weather.

Specifications

Image System	
Image Sensor	1/2.7" 2MP image sensor optimized for low-light performance
Image Compression Method	Triple Streaming : H.264 / MPEG4 / Motion JPEG
Maximum Framerate vs. Resolution	HDTV 1080p (1920x1080) at 15 fps (NTSC) and 12.5 fps (PAL), 2MP 16:9 (1280x720) at 30 fps (NTSC) and 25 fps (PAL)
Lens	Built-in Mechanical IR Cut Filter varifocal lens f=3~9mm, F1.2 (Mega pixel lens)
IRIS Control	DC IRIS
View Angle	H: 93°(Wide)~31.7°(Tele)/V:68.4°(Wide)~23.8°(Tele)
View Angle Adjustment	Pan:0°-355°(Max.), Tilt:0°-70°(Max.), Rotate:0°-355°(Max.)
Electric	
Shutter Time	1/10,000s to 1/3.75s selectable (60Hz); 1/10,000s to 1/3.125s selectable (50Hz)
Audio	Two-way Mono Audio, Full-duplex, G.711 PCM 8kHz
Alarm	External input
Day/Night Mode	Mechanical (ICR) D/N control; Auto Switch
Minimum illumination	IR LED OFF: 0.06 Lux @10IRE; 0.24Lux @50IRE (shutter speed: 1/15sec) IR LED ON: 0lux
IR LED	IR LED 20pcs (850nm)
IR Distance	25 meters (82 ft.)
IR turn on status	Under 10 lux by auto control
LED Life	More than 10,000 hours (50°C)
Video Port	BNC X1, 1.0Vp-p, 75Ω / RCA x 1
Video Output	NTSC: 720 X 480 @30fps; PAL: 720 X 576 @25fps
Image Enhance	Exposure Mode: Auto/Manual White Balance: Auto/Manual, Backlight Compensation: 5x5 zones, Sharpness, saturation, brightness, contrast: 255 level sensitivity
Feature Brief	
Digital WDR	Yes; 5 level sensitivity
Privacy Zone	Yes; customized threshold privacy zone
Intelligent Video	Audio detection / Blur detection / Ethernet Detection/ Smart Encoding/ Smart Focus/ e-PTZ/ Event Management
Alarm Detection	Motion Detection: 5 x 5 zones, 5 level sensitivity or customized threshold, Audio Detection: 5 level sensitivity or customized threshold, Blur Detection: customized threshold, External Input
Alarm Event	File upload via FTP, SMTP and micro SD/SDHC Card, Notification via email, HTTP and TCP, External output activation, Video and audio recording to micro SD/SDHC Card
Text Overlay (to be developed)	Yes
Image Orientation	Mirror, Flip
Other	Snapshot
Local Storage	
Memory Card	Micro SD/SDHC Card up to 32 GB
SD Card Overwrite	Yes
SD Card Store Category	Alarm / Motion / Schedule / Un-interrupt recording
Power supply	
Power Requirement	DC 12V & AC 24V ± 10% / PoE (IEEE 802.3af) Class 3
Power Connector	Screwless Terminal block
Power consumption (Max.)	8W
	8 W (heater off), 20 W (heater on)
Environment	
Operating Temperature	-10°C ~ 50°C (-14°F ~ 122 °F)
	-40°C ~ 50°C (-40°F ~ 122 °F)
Operating Humidity	10~ 90% RH
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140 °F)
Regulatory	CE, FCC, RoHS
Network	
Ethernet	10Base-T/100Base-TX Ethernet connection for LAN / WAN, RJ-45
Internet Protocol	IPv4, TCP/IP, UDP, HTTP, SMTP, DNS, DHCP, NTP, FTP, RTP,RTSP, ICMP, UPnP
Browser	IE browser 6.0 or above
I/O connector	
Alarm Port	Terminal block 2 in / 1 out
Audio In / Out port	3.5mm Phone Jack x 2
Reset	Within 5 sec for rebooting system; more than 5 sec for loading default
Mechanism	
Dimensions(ΦxH)	Φ141mmx 121mm (Φ5.55" x 4.76")
Weight	1.3kg (2.87 lb)
Protection Class	IP67, IK10, vandal-proof
Option	Without Heater
	With Heater
Order Information	NTSC model: NDR891-HN5-MES; PAL model: NDR891-HP5-MES
	NTSC model: NDR891H-HN5-MES; PAL model: NDR891H-HP5-MES
Accessory	
Mount Type	Surface mount: standard package support, Pedent mount: thread 1", Wall mount:Bracket SAB755BP

Dimensions

