



Specification

Item	NVS121
Remote management	Configuration and system log can be accessed via web browser and Ftp application remotely
Networking	
Protocol	TCP/IP, HTTP, ARP, PPPoE, DDNS, DHCP, RTP/RTSP, IGMP
Modem	-
Ethernet	10/100 base T Ethernet
Video	
Compression	MPEG4 ASP compliant
Video input	1 BNC composite video input with NTSC / PAL auto sensing
Analog output	1 Vpp composite output 75ohm.
Image size	352 x 240, 720 x 480- NTSC 352 x 288, 720 x 576- PAL
Image quality	CIF to D1
Others	Watch dog timer 5 sec.
	2 DI/ 2 DO event triggered via Ethernet
	Layer 2, 3
Audio	-
Frame rate	352 x 240 @ 30fps, 720 x 480 @ 30fps - NTSC
	352 x 288 @ 25fps, 720 x 576 @ 25fps - PAL
RS485	1 x RJ-45
Viewing system requirement	
Protocol	Standard internet TCP/IP
Operating system	Win 2000, Win XP
Browser	Internet Explorer 5.X or above
Security	User authorization needed for protecting camera access
Pan/tilt/zoom control	Automatic PTZ camera detection with Pelco-D protocol
	Clear data command driver is supported
LED indicator	Hearbeat, status, network
General	
Power input	12V / 0.625A / 7.5W
Operating temperature	-10 ~ 60 (32 ~140)
Operating humidity	10% ~ 90%
Dimensions	85.5mm x 52mm x 1.6mm (3.37" x 2.05" x 0.06")