



Resolution	3MP	2MP	3MP	3MP	3MP
Model No.	SLV003	SLV004	SLV005	SLV006	SLV525
Model Name	3 Megapixel Lens 2.8 - 12mm	2 Megapixel Lens 3.3 - 12mm	3 Megapixel Lens 7 - 22mm	3 Megapixel Lens 8 - 80mm	3 Megapixel Lens 2.8 - 8mm
Mount	CS Mount	CS Mount	CS Mount	C Mount	CS Mount
Focal Length	2.8 - 12mm	3.3- 12mm	7- 22mm	8 - 80mm	2.8 - 8mm
Aperture(F)	F1.4	F1.4	F1.4	F1.6	F1.2
Sensor Format	1/2.7"	1/2.7"	1/2.7"	1/2"	1/3"
Horizontal angle of view	100°~28°	100°~28.4°	41.0° ~ 14°	44°33' - 4°42'	100° - 35°03'
IRIS Control	DC IRIS	DC IRIS	DC IRIS	DC IRIS	DC IRIS
IR Corrected	YES	YES	YES	YES	YES
Supported Cameras	NCB855PRO, NCB858	NCB855PRO	NCB855PRO, NCB858	NCH517	NCB855PRO & NCB858
Dimensions	Ø33.0mm x 46.4mm x 42.1mm	Ø29 x 44.2 x 43.5mm	Ø33.0 x 41.4 x 46.5mm	Ø54mm x 89.3mm	Ø40.8mm x 52mm
Weight(g)	39g	59.9g	39g	180g	50g

Resolution	D1	D1	D1	D1	D1	D1	D1
Model No.	SLV521	SLV522	SLV524	SLV524PRO	SLV532	SLV562	SLV563
Model Name	2.7X Vari-focal lens		4.4X Vari-focal lens	4X Vari-focal lens	7X Vari-focal lens	12X Vari-focal lens	12X Vari-focal lens
Mount	CS Mount	CS Mount	CS Mount	CS Mount	CS Mount	CS Mount	C Mount
Focal Length	3 - 8mm	3 - 8.5mm	2.7 - 12mm	2.8 - 12mm	7.5 - 50mm	5 - 60mm	10 - 120mm
Aperture(F)	F0.95	F1.0	F1.2	F1.2	F1.3	F1.6	F1.6
Sensor Format	1/3"	1/3"	1/3"	1/3"	1/3"	1/3"	1/2"
Horizontal angle of view	94.3° - 35.9°	90.5° - 33.6°	97.4° - 23.8°	98.5° - 23.8°	36.6° - 5.64°	52.5° - 4.6°	34.7° - 3.1°
IRIS Control	DC IRIS	DC IRIS	DC IRIS	DC IRIS	DC IRIS	DC IRIS	DC IRIS
IR Corrected	YES	YES	YES	YES	YES	YES	NO
Supported Cameras	-	-	-	-	-	SCB265iPRO, SCR515PRO	SCB265iPRO, SCR515PRO
Dimensions	Ø38.0mm x 48mm x 49.7mm	Ø35mm x 47.4mm x 46mm	Ø39mm x 50mm x 57mm	Ø35mm x 47.9mm x 53.3mm	Ø38mm x 50.1mm x 55.2mm	42(W) x 47(H) x 62.5(L) mm	Ø55.0mm x 64.3mm x 123.2mm
Weight(g)	64g	54g	72g	58g	68g	123g	350g