

MonoDome Camera D24



Fits In. Watches Out.

Inconspicuous surveillance with state-of-the-art technology. The D24 FixDome from MOBOTIX adapts perfectly to any task. Exchangeable lenses, various mounting and configuration options including vandalism set support unlimited application possibilities.



MOBOTIX HiRes video replaces up to 6 cameras ...

- Attractively designed FixDome camera featuring exchangeable lenses from Tele to Wide Angle
- Numerous installation options both indoor and outdoor
- On-wall set with space for extension modules (battery, UMTS, WLAN, etc.)
- Integrated DVR with HiRes video recording (4 GB MicroSD card incl.)
- Robust, low-maintenance and weatherproof from -30 to +60 °C (-22 to +140 °F), (IP65)
- Digital continuous zoom, pan and tilt
- Can be upgraded to an intercom system with the MOBOTIX ExtIO module

... starting at \$648* incl. video management software

*MSRP (Manufacturer's suggested retail prices) • Prices ex-works Charlston, South Carolina (SC), USA (EXW) • Excluding VAT and any other handling charges • Information subject to change without notice! • © MOBOTIX AG

D24 – Compact, Cost-Efficient And With High Resolution

The many, easy-to-replace lens options of the D24 provide a tailored solution for different types of applications. A robust dome camera (IP65) with optional vandal-proof, wall-mount and in-ceiling installation sets.

Technical Specifications D24



The HiRes Video Company

| Technical Specifications D24 MonoDome | |
|--|---|
| Models | Basic, IT, IT-Night, Sec, Sec-Night |
| Lenses | 22 to 135 mm format, horizontal angle 90° to 15° |
| Sensitivity | Color: 1 lux (t=1/60 s), 0.05 lux (t=1/1 s) B/W: 0.1 lux (t=1/60 s), 0.005 lux (t=1/1 s) |
| Sensor | 1/2" CMOS, progressive scan |
| Max. image resolution | Color: 2048 x 1536 (3MEGA), B/W: 1280 x 960 (MEGA) |
| Image format | 2048 x 1536, 1280 x 960, 1024 x 768, 800 x 600, 768 x 576 (D1), 704 x 576 (TV-PAL), 640 x 480, 384 x 288, 352 x 288, 320 x 240, 160 x 120; free image format selection (e.g. 1000 x 200 for skyline) |
| Max frame rate (M-JPEG) (Live/Recording) | VGA: 25 fps, TV-PAL: 18 fps, MEGA: 8 fps, 3MEGA: 4 fps |
| Video stream (MxPEG) (Live/Recording/Audio) | VGA: 30 fps, TV-PAL: 30 fps, MEGA: 30 fps, 3MEGA: 20 fps |
| Image compression | MxPEG, M-JPEG, JPEG, H.263 (only Video-VoIP) |
| Internal DVR | MicroSD slot (camera-internal video recording up to 32GB) |
| External storage | Directly on NAS and PC/Server without additional recording software |
| Software (inclusive) | Video management software MxEasy, Control room software MxControlCenter |
| Image processing | Backlight compensation, automatic white balance, image distortion correction, video sensor (motion detection) |
| Virtual PTZ | Digital Pan/Tilt/Zoom, continuous 8x zoom |
| Alarm/Events | Triggering of events by integrated multiple-window motion detection, external signal, temperature sensor, notification over email, FTP, IP telephony (VoIP, SIP), visual/acoustic alarm, pre- and post-alarm images |
| Audio | Optional via ExtIO, lip-synchronous audio, two-way speaker, audio recording, video VoIP supported |
| Interfaces | Ethernet 10/100, USB, MxBus |
| Video phone | VoIP, SIP, two-way speaker, remote control via DTMF signaling, event notification |
| Security | User-/Group management, HTTPS/SSL, IP address filter, IEEE 802.1x, intrusion detection, digital image signature |
| Certificates | EMC (EN50121-4, EN55022, EN55024, EN61000-6-2, FCC part15B, AS/NZS3548) |
| Power supply | Power over Ethernet (IEEE 802.3af): PoE class variable depending on operating mode; power consumption: typ. 3 W; with PoE switch/MOBOTIX PoE adapter |
| Operating conditions | IP65 (DIN EN 60529), -30 to +60 °C (-22 to +140 °F) |
| Dimensions | Ø x H: 16 x 8.6 cm, Weight: ca. 350 g |
| Standard delivery | Housing (high-resistance composites – PBT), white, shockproof polycarbonate dome (transparent), free choice of lenses, mounting parts, allen wrench, patch cable - 50 cm, manual, software, 4 GB MicroSD (except Basic) |

Technical information subject to change without notice.

| Available Accessories D24 MonoDome | | | | | |
|--|---|--|--|---|---|
| In-Ceiling Set MX-OPT-IC  <ul style="list-style-type: none"> Consists of in-ceiling mount and mounting parts Easy mounting from front Ø 150 mm installation dimension It can be ordered with stainless steel cover | On-Wall Set MX-OPT-AP  <ul style="list-style-type: none"> Consists of On-Wall mount and mounting parts Protects the cabling 165 mm x 37 mm | Vandalism Set MX-D24M-Vandal-ESMA  <ul style="list-style-type: none"> Reinforced dome (3 mm Polyc.) Stainless steel vandalism housing in polished, matt or in powder-coated white, silvergray or black | Outdoor Wall Mount MX-OPT-WH  <ul style="list-style-type: none"> Weatherproof (IP65) Covers RJ45 wall outlets Space for expansion modules (WLAN) | Pole Mount MX-OPT-MH  <ul style="list-style-type: none"> 3 mm stainless steel, white 2 stainless steel straps for pole diameter 60-180 mm, incl. mounting parts | ExtIO Extension Module MX-ExtIO  <ul style="list-style-type: none"> Microphone/Speaker PIR sensor for motion deflection, temperature sensor 2 signal inputs, 2 signal outputs, 2 illuminated buttons |

| | L22 Super Wide Angle 90° | L32 Wide Angle 60° | L43 Wide Angle 45° | L65 Tele 31° | L135 Tele 15° |
|--------|---|---|---|--|---|
| Lenses |  |  |  |  |  |
| | approx. 90°H x 67°V at 10 m appr: 20.0 x 13.3 m | approx. 60°H x 45°V at 10 m appr: 11.5 x 8.2 m | approx. 45°H x 34°V at 10 m appr: 8.2 x 6.1 m | approx. 31°H x 23°V at 10 m appr: 5.5 x 4.0 m | approx. 15°H x 11°V at 10 m appr: 2.6 x 1.9 m |

D24 – Compact, Cost-Efficient And With High Resolution

The many, easy-to-replace lens options of the D24 provide a tailored solution for different types of applications. A robust dome camera (IP65) with optional vandal-proof, wall-mount and in-ceiling installation sets.