

## WV-CP284

Static Cameras

Built-in Super Dynamic III Function

High Definition - 540 and 570 line resolution

Signal to Noise Ratio of 50dB

Auto Image Stabilizer Function

Scene change Detection Alarm



1/3" Super Dynamic III Colour Surveillance Camera

null

### General

Type	Colour Surveillance Camera
Pick-up Device	1/3-type interline transfer CCD

### Effective Pixels

Horizontal	752.0
Vertical	582.0

### Scanning Area [mm]

Horizontal	4.9
Vertical	3.7
Signal	PAL
Synchronization	Internal (INT), Multiplexed Vertical Drive (VD2), Line-Lock (LL), selectable
Scanning Mode	2:1 interlace

### Scanning Frequency

Horizontal [KHz]	15.625
Vertical [Hz]	50.0

### Resolution

Horizontal	540 TV lines (Colour)
------------	-----------------------

Vertical	-
Dynamic Range	-
Signal-to-Noise Ratio	50 dB minimum (AGC: OFF)
Minimum Illumination (Colour)	0.8 lux
Minimum Illumination (B/W)	-
Weather Protection	-

## Power Source

Voltage AC [V]	24
Voltage DC [V]	12.0
Frequency [Hz]	50.0
Power Consumption [W]	2.7

## Ambient Operating Temperature [degrees C]

Minimum	-10.0
Maximum	50.0

## Ambient Operating Humidity [%]

Minimum	0.0
Maximum	90.0

## Dimensions [mm]

Width	67.0
Height	65.0
Depth	139.5
Weight [kg]	0.35
Finish	-

## Main Functions

Controller Interface	Coaxial
Auto Gain Control (AGC)	Always On
Zoom Speed	-
Focus Speed	-
Iris / Light Control	ALC/ELC
Shutter	-
Motion Detector	-
Auto Focus	-
Back Light Compensation (BLC)	ON/OFF
Sensitivity Enhancement	-
White Balance	ATW
Camera Title	16 alphanumeric characters
Privacy Zone	-

<b>Image Stabilizer</b>	-
<b>Adaptive Black Stretch</b>	ON/OFF
<b>Detail / Aperture Level</b>	-
<b>Colour/Mono Switching</b>	ON/OFF
<b>Mirror</b>	-
<b>Language Setting</b>	English, German, French, Italian, Spanish, Russian, Chinese, Japanese

## Lens

<b>Type</b>	CS-mount
<b>Zoom Ratio</b>	-
<b>Iris Range / Aperture Ratio</b>	-

## Angular Field of View

<b>Horizontal</b>	-
<b>Vertical</b>	-
<b>Maximum Aperture Ratio</b>	-

## Input/Output

<b>Video Output</b>	VBS: 1.0V [p-p] PAL composite 75 Ohms (BNC plug)
<b>Alarm Output</b>	-