

WV-NP240
Network Static Cameras

Dual MPEG4 and JPEG digital signal output

Built in SD memory card slot for FTP backup

Built in network interface

Image refresh rate up to 30 fps

Designed for Power over Ethernet - PoE



Network Security Colour Camera with PoE

null

General

Type	Network Security Colour Camera with PoE
Pick-up Device	Progressive scan type CCD sensor

Scanning Area [mm]

Horizontal	5.79
Vertical	4.89
Signal	PAL
Synchronization	-
Scanning Mode	-

Resolution

Horizontal	-
Vertical	-
Dynamic Range	-
Signal-to-Noise Ratio	-
Minimum Illumination (Colour)	1.1 lux
Minimum Illumination (B/W)	-
Weather Protection	-

Power Source

Voltage AC [V]	220-240
Voltage DC [V]	0.0
Frequency [Hz]	50.0
Power Consumption [W]	5.0
PoE (Power over Ethernet)	PoE (IEEE802.3af compliant)

Ambient Operating Temperature [degrees C]

Minimum	-10.0
Maximum	50.0

Ambient Operating Humidity [%]

Minimum	0.0
Maximum	90.0

Dimensions [mm]

Width	72.0
Height	65.0
Depth	158.0
Weight [kg]	0.47

Main Functions

Controller Interface	-
Control Functions	-
Auto Gain Control (AGC)	Always ON
Zoom Speed	-
Focus Speed	-
Iris / Light Control	ALC
Shutter	AUTO
Sensitivity Enhancement	16x max. (AUTO or FIX)
White Balance	AUTO/HOLD
Adaptive Black Stretch	-
Camera Title	-
Privacy Zone	-
Image Stabilizer	-
Colour/Mono Switching	-
Language Setting	English, German, French, Italian, Spanish, Russian, Chinese, Japanese

Lens

Type	ALC lens drive, DC drive, CS-mount
Zoom Ratio	3x with digital zoom

Network

Network Interface	10Base-T/100Base-TX, RJ45 connector
-------------------	-------------------------------------

Image Resolution	JPEG: 1,296 x 960 / VGA (640 x 480 pixels) / QVGA (320 x 240 pixels), MPEG-4 VGA (640 x 480 pixels) / QVGA (320 x 240 pixels)
Image Compression	MPEG-4: (Image quality: LOW/NORMAL/FINE), (Transmission type: UNICAST/MULTICAST), JPEG: (Image quality: 10 steps), (Transmissi- on type: PULL/PUSH)
Image Refresh Rate	0.1 ips ~ 30 ips
Audio Compression	G.726 (ADPCM) 32 kbps / 16 kbps
Bandwidth Control	64 kbps/ 128 kbps/ 256 kbps/ 512 kbps/ 1,024 kbps/ 2,048 kbps/ 4,096 kbps/ unlimited
Supported Protocol	TCP/IP, UDP/IP, HTTP, FTP, SMTP, DHCP, DNS, DDNS, NTP, SNMP, RTP
Supported Operating System	Microsoft Windows 2000 Professional SP4, Microsoft Windows XP Ho- me SP2, Microsoft Windows XP Professional SP2
Supported Browser	Internet Explorer 6.0 SP2 (Windows XP Home/Professional SP2), Inter- net Explorer 6.0 SP1 (Windows 2000 Professional SP4)
FTP Client	-
Multi Screen	4 x screens, 2 x groups
SD Memory Card Slot	Manual REC/Alarm REC/Backup upon network failure. Compatible SD card: Panasonic 64MB, 128MB, 256MB, 512MB, 1GB, 2GB model. SD- HC standard card not supported.
Alarm Email	Yes
Time Date Display	-
Security Measures	-
Input/Output	
Video Output	VBS: 1.0V [p-p]/ 75 Ohms composite signal, BNC connector