



## RVX-PSU-ALM-16-W

### PSU with 16 hard wired and 16 wireless alarm inputs-3 alarm outputs

16 Alarms support combination of both hard wired and wireless inputs. Wireless receiver within the PSU is directly compatible with the Redvision range of wireless PIR's. Single or multiple domes can be triggered from a single wireless PIR activation. Alarm inputs can activate presets and tours. Alarms can be masked on a timed basis for weekend and weekday operation. 3 alarm 0V relay outputs for ALARM, WASH and AUX.

### Key Features

- Compatible with Redvision RV wireless PIR's
- 16 Wireless/hard wired inputs
- Connections via pluggable terminal blocks
- IP 66 weatherproof enclosure
- Alarm handling/masking
- 3 alarm outputs, ALARM, WASH, AUX
- On board LEDs for RS 485 diagnostics
- On board Lightning protection

### Specification

#### Mechanical

Connections	Pluggable terminal blocks and BNC connections
Glands	1 x 20mm Gland, 1 x 16mm Gland, 3 x 12mm Glands

#### Environmental and physical

Material	ABS
Operating Temperature	-35°C to +50°C
Dimensions	125 x 140 x 100mm (l x w x h)
Weight	1 Kilo

#### Power

Input	110Vac to 240Vac
Output	24Vdc 60VA