

Color Quad Switcher

SCQ-041P



Features

- 4Ch camera input/2Ch video output
- 240 TV lines of horizontal resolution(quad display only)
- An adjustable date/time display feature is provided
- Each channel can be viewed in single display mode
- In auto switcher mode, each channel switches automatically for viewers
- The channel loss feature provides a buzzer sound and displays the channel loss on the screen
- You can make an important-scene freeze in quarter screen mode by using the "FREEZE" key
- Alarm and video loss occurrence details is recorded in "ALARM/LOSS" list(Max. 8 events)
- RS-232C remote control

Video Security Systems


SCQ-041P



Specifications

MODEL	SCQ-041P	
Video Input	Camera : 4Ch (BNC Type), Color or Black and White, Loop Through Out x 4(BNC), Auto Termination 1.0Vp-p, 75 Termination	
Video Output	Monitor 1	Quad, 1.0Vp-p, 75 Termination
	Monitor 2	The user can select from Quad, Full, Auto switcher mode 1.0Vp-p, 75 Termination
Horizontal Resolution	240TV Lines(Quad Display Mode)	
Remote control	RS-232C (D-SUB 25Pin) Baud Rate:9600bps, Parity Bit:None Data Bit:8Bit, Stop Bit:1Bit	
Alarm Input	Input 4Ch, TTL "LOW" Level Active	
Alarm Output	Active Make Alarm Reset : TTL "LOW" Level, Pulse Width = Above 150ms	
Alarm Duration	5,10,20,30,60,90,120,180sec, User must set alarm duration in the menu	
Auto Switcher	0 ~ 30sec(User must set time in the menu) You can turn the Auto Switcher ON or OFF for each channel	
Character Indication (OSD)	Title	Each channel indicates maximum 8 characters (Alpha-Numeric, Special Characters)
	Date & Time	Year/Month/Day/, Hour:Minute:Second
	Alarm Indication	"A"
	Channel Loss	"LOSS"
Video Loss Detection	4 Channels	
Quantization Bit number	8Bit(256 Steps)	
Sampling of Frequency	28.63636MHz	
Operating Temperature	0 ~ +40	
Operating Humidity	20 ~ 85% RH	
Power Requirement	AC100~240V, 50/60Hz	
Power Consumption	Less than 10W	
Weight	Approx. 3.8Kg(without packing)	
Dimensions(W x H x D)	430 x 44 x 350mm	

Dimensions



ISO9001 : 1994
File No. - A8150



Samsung Headquarters
Samsung Electronics Co., Ltd.
416, Maetan-3Dong, Paldal-Gu
Suwon City, Kyungki-Do, Korea 442-742
TEL : 82-31-200-5504, 5578 FAX : 82-31-200-5594
<http://samsungelectronics.com/security/cctv/>

Distributed by:

* Design and specifications are subject to change without notice.