

SAMSUNG

High Performance IR Illuminator



IR Illuminator SPI-10/30

- IR illuminator can be applied with Samsung positioning system (SPU-2370, SPU-VAC/VAC1)
- Viewable length of 100m (328.1 ft) : SPI-10 /
70m (229.66 ft) : SPI-30
- Radiation angle of 10° : SPI-10 /
30° : SPI-30
- To provide additional light in dark surroundings
- Dust/Water proof rated to IP66
- Operating temperature of -40°C ~ 50°C



		SPI-30	SPI-10
General	IR Distance	70M	100M
	Radiation Angle	30°	10°
	LEDs	High efficiency 32 LED array	
	Wave length	850nm	
	Main material	Body : Aluminum Front Cover : Plastic(black)	
Electrical	Ingress Protection	IP66	
	Power	Dual (24V AC / 12V DC)	
	Power consumption	22W	
Mechanical	Size	179(W) x 147.3(H) x 59.5(D) mm	
	Working temperature	-40°C ~ 50°C	
	Net weight	880g	

SAMSUNG

SAMSUNG TECHWIN CO., LTD.
701, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do Korea 463-400
Tel : +82-70-7147-8741-8749, 8752-8760 Fax : +82-31-8018-3745
www.samsungsecurity.com www.samsungcctv.com

SAMSUNG TECHWIN AMERICA Inc.
100 Challenger Rd, Suite 700 Ridgefield Park, NJ 07660
Toll Free : +1-877-213-1222 Direct : +1-201-325-6920
Fax : +1-201-373-0124
www.samsungcctvusa.com

SAMSUNG TECHWIN EUROPE LTD.
Samsung House, 1000 Hillswood Drive, Hillswood Business Park
Chertsey, Surrey, UNITED KINGDOM KT16 0PS
Tel : +44-1932-45-5300 Fax : +44-1932-45-5325



The **Eco mark** represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONICS CO., LTD.
No.11 Wei 6 Street, Micro-Electronic Industrial Park
Jingang Road, Tianjin, P.R. CHINA 300385
Tel : +86-22-23887788 Fax : +86-22-23887788

■ DISTRIBUTED BY



I.E-1204