



IP PTZ dome with D/N & wide dynamic range (outdoor)

Siqura HD26 WDR

Features

- Outdoor High Speed Network PTZ dome
- Tri-stream support- Dual-MPEG-4 / MJPEG
- 35x Optical Zoom/12x digital zoom
- Day/Night with IR-cut filter
- Wide Dynamic Range
- Back Light Compensation
- Electronic Image Stabilization
- 400°/second Preset targeting
- 360° continuous rotation
- 256 presets/1 programmable cruise
- 8 alarm in/1 output
- Two-way audio
- 8 Privacy Masks
- Analog Output
- Polycarbonate bubble
- 24 VAC



Bracket sold separately

Description

The Siqura® HD26 WDR ensures excellent pictures even in the most difficult circumstances by offering features such as day/night, digital slow shutter, wide dynamic range, and image stabilizer.

Triple Streaming

The versatile HD26 WDR is capable of streaming dual MPEG-4 and MJPEG simultaneously. Each stream is optimized for its purpose, e.g., high-quality MJPEG live viewing, low-bandwidth MPEG-4 storage, and low-resolution MJPEG for web applications or remote devices (e.g., PDAs).

High-Speed Dome

This high-speed PTZ dome has 35x autofocus zoom lens with the 12x digital zoom. Because the lens can move in almost any direction (pan and tilt), this camera offers a wide view precise without missing the smallest details. In addition, the precision 400° per second pan and tilt drive technology offers almost instant preset positioning.

Day/Night and Backlight Compensation

The HD26 WDR is provided with an automatic Day/Night functionality, which is used in low light situations and a Backlight Compensation functionality for use in different scenes. This means, the HD26 WDR provides a clear picture for the operator, no matter what the lighting situation is.

Audio, I/O Contacts and Analog Output

By combining streaming video with duplex audio and I/O contacts over IP, the HD26 WDR provides all the interfaces necessary for any IP CCTV application. The balanced audio inputs/outputs are suitable for all industrial audio systems. With its analog output, the HD26 WDR is a hybrid solution and can provide local video for a public view monitor or local DVR.

Image Stabilizer

When the high-speed dome is in its maximum zoom range, every small movement of the camera gives a relatively large movement in the picture. The image stabilizer digitally compensates this movement for a stable picture. This feature is especially useful for pole-mounted domes.

Privacy Masks

Privacy masks cover sections of the image and shrink or grow according to the camera's zoom. This feature is often requested for such situations as city center surveillance and point of sale keypads.

Siqura Surveillance Solutions

The Siqura® HD26 WDR is part of Siqura, a complete collection of surveillance equipment and solutions. Siqura offers video codecs/servers, IP cameras, video management, network storage, and configuration software.

Ordering information

| Model | Description | Zoom | Privacy Masks | NTSC/PAL |
|--------------------|---|------|---------------|----------|
| Siqura HD26 WDR /N | IP high-speed PTZ Dome Camera, Wide Dynamic Range, day/night, IP66, incl. sunshield | 35x | 8 | NTSC |
| Siqura HD26 WDR /P | IP high-speed PTZ Dome Camera, Wide Dynamic Range, day/night, IP66, incl. sunshield | 35x | 8 | PAL |

Siqura HD26 WDR

Technical Specifications

Camera

| | | |
|------------------------|----------------------------------|------------|
| Image sensor | 1/4" CCD | |
| Optical zoom | 35x | |
| Digital zoom | 12x | |
| Resolution | NTSC | PAL |
| Effective pixels | 380k | 440k |
| Horizontal resolution | 540 TVL | 540 TVL |
| Electronic shutter | 1/2~1/30 k s | |
| D1 | 720x480 | 720x576 |
| 1/2D1 | 352x480 | 352x576 |
| 2CIF | 720x240 | 720x288 |
| CIF | 352x240 | 352x288 |
| QCIF | 176x120 | 176x144 |
| Synchronization | Internal/line lock | |
| Video output | 1.0 Vpp/75Ω, BNC | |
| S/N ratio | >50 dB (AGC off) | |
| Minimum illumination | 0.05 lux (color), 0.01 lux (B/W) | |
| Focal length | 3.4~119mm | |
| Focus mode | Auto/ manual | |
| White balance | Auto/ manual | |
| Iris control | Auto/ manual | |
| AGC control | Auto/ manual | |
| Backlight compensation | On/ Off | |

Video

| | |
|-------------------------|---|
| Number of video streams | 2x MPEG-4 and/or MJPEG |
| Frame rate | 1 to 30 fps |
| Compression algorithm | MPEG-4 SP Layer 5 (ISO/IEC 14496-2), MJPEG |

Audio

| | |
|---------------|--|
| Two-way audio | Line out, Line in/mic in (jack Ø3.5 mm) |
|---------------|--|

Functions

| | |
|----------------------------|---------|
| Motion detection | On/ Off |
| Day/ Night (IR-cut filter) | On/ Off |
| Digital slow shutter | On/ Off |

Contacts

| | |
|----------------|------------------------------------|
| Alarm input | 8 |
| Alarm output | 1 |
| Alarm reaction | Preset, Sequence, Auto pan, Cruise |

Network

| | |
|-----------|---|
| Interface | RJ45 |
| Protocol | MPEG-4 ES, RTP, UDP, IP, DHCP, IGMPv2, RTSP, (S)NTP, MX/IP, HTTP, SNMP v2 |

Pan/Tilt

| | |
|-------------------------|---------------------------------------|
| Pan travel | 360° endless |
| Tilt travel | -10° ~ 190° |
| Preset speed | 400°/s |
| Manual speed | 90°/s |
| Presets | 256 presets |
| Preset accuracy | 0.225° |
| Cruise | 1 |
| Sequence | 8 |
| Auto pan | 4 |
| Proportional pan & tilt | On/ Off |
| Resume after power loss | Yes |
| Zone title | 16 |
| Home function | Preset, Sequence, Auto pan, Cruise |
| Auto flip | Digital/ Mechanical/ Off |

Mechanical

| | |
|-----------------------|--------------------------------------|
| Dimension (h x w x d) | Ø7.5 x 11.9 in. (Ø190 x 302.5 mm) |
| Weight | 13.2 lbs. (6 kg) |
| Color | RAL-9003 (Signal White) |

Environmental


| | |
|-----------------------|-------------------------------------|
| Operating Temperature | -49°F to +122°F (-45°C to +50°C) |
|-----------------------|-------------------------------------|

Powering

| | |
|-------------------|--|
| Power consumption | 73W |
| Power | 19.2 - 28.4 VAC (24VAC nominal +/- 20%) |

Siqura HD26 WDR

Technical Drawing



Ordering Information Accessories

| Model | Description |
|---|---|
| Siqura PA02 /EU Siqura PA02 /US Siqura PA03 | Power adapter 220~235 VAC to 24 VAC /3A for MD- and HD-series with use of heater (outdoor), with EU plug. Power adapter 100~115 VAC to 24 VAC /3A for MD- and HD-series with use of heater (outdoor), US plug. Power adapter 110/220 VAC to 24 VAC /3A in water-resistant housing |
| Siqura WM01 Siqura WM02 /HD Siqura WM03 Siqura WM05 Siqura WM06 | Mini pendant for MD- and HD-series Mount kit for indoor HD-series, compatible with CM01, CM02 and WM03 Gooseneck tube Corner plate, compatible with WM01 and WM03 Wall box mounting, compatible with WM01 and WM03 |
| Siqura PM01 Siqura PM02 Siqura PM03 Siqura PM04 Siqura PM05 | Pole thin direct mounting, compatible with WM01 and WM03 Pole wide direct mounting, compatible with WM01 and WM03 Pole thin box mounting, compatible with WM01 and WM03 Pole wide box mounting, compatible with WM01 and WM03 Swan neck tube |
| Siqura CC13 /IP | 1.3M Cable, BNC/Audio/Power jacks, 22 pins for WM03 and PM05 |

