



Corporate Headquarters
Optelecom-NKF, Inc.
USA

Telephone +1 301.444.2200
Telefax +1.301.444.2299
E-mail sales.us@optelecom-nkf.com

European Corporate Office
Optelecom-NKF B.V.
The Netherlands

Telephone +31 182 592 333
Telefax +31 182 592 123
E-mail sales.nl@optelecom-nkf.com

European Sales Offices

The Netherlands
+31 182 592 333
sales.nl@optelecom-nkf.com

France
+33 1 47 66 88 65
sales.fr@optelecom-nkf.com

United Kingdom
+44 1204 546 635
sales.uk@optelecom-nkf.com

Spain
+34 91 676 8164
sales.es@optelecom-nkf.com

Germany
+49 2303 94 33 44
sales.de@optelecom-nkf.com

Italy
+39 0331 268202
sales.it@optelecom-nkf.com

Middle East

United Arab Emirates
+971 4 5015741
sales.ae@optelecom-nkf.com

Asia

Singapore
+65 6264 7501
sales.sg@optelecom-nkf.com



Americas Sales Offices

Northeast U.S. / Eastern Canada
+1 301 444 2217
sales.us.northeast@optelecom-nkf.com

Northwest U.S. / Western Canada
+1 301 444 2209
sales.us.northwest@optelecom-nkf.com

Mid-Atlantic / Midwest U.S.
+1 301 444 2214
sales.us.midatlantic@optelecom-nkf.com

Southwest U.S.
+1 301 444 2228
sales.us.southwest@optelecom-nkf.com

Southeast U.S.
+1 301 444 2215
sales.us.southeast@optelecom-nkf.com

Latin America
+1 301 444 2277
sales.la@optelecom-nkf.com

Optelecom-NKF B.V., 2008 www.optelecom-nkf.com



Siqura Camera Line Card

Analog & Network Cameras

- Box Camera
- Fixed Dome
- Mini Dome
- High-Speed Dome



WWW.SIQURA.COM

	Analog Camera								Network Camera															
	Box		Fixed dome	Mini dome		High-speed dome			Box				Fixed dome				Mini-dome		High-Speed dome					
Type	BC10	BC12	FD12	MD10	MD12	HD10	HD12	HD16WDR	BC20	BC22	BC24	BC24WDR	FD20	FD22	FD24	FD24WDR	MD20	MD22	OpteliDome	HD20	HD22	HD26WDR		
Image sensor	1/3" Super HAD CCD		1/3" Super HAD CCD	1/4" Exview CCD		1/4" CCD			1/3" CCD	1/3.8" CMOS	1/3" CCD			1/3" CCD	1/3.8" CMOS	1/3" CCD			1/4" Exview CCD		1/4" CCD			
Optical zoom	-	-	-	12x	12x	26x	26x	35x	-	-	-	-	-	-	-	-	12x	12x	30X	26x	26x	35x		
Digital zoom	-	-	-	10x	10x	12x	12x	12x	-	-	-	-	-	-	-	-	10x	10x	10X	12x	12x	12x		
Focal length	-	-	3.7 - 12 mm	4 - 48 mm	4 - 48 mm	3.5 - 91 mm	3.5 - 91 mm	3.4 - 119 mm	-	-	-	-	3.7 - 12 mm	3.7 - 12 mm	3.7 - 12 mm	3.7 - 12mm	4 - 48mm	4 - 48mm	3.3 - 99 mm	3.5 - 91 mm	3.5 - 91 mm	3.4 - 119 mm		
Min. illumination	0.2 Lux @ F1.2	0.2 Lux/ 0.03 lux (B/W)	0.2 Lux/ 0.03 lux (B/W)	1 lux/0.1 lux (B/W)		0.07 lux/ 0.01 lux (B/W)		0.05 lux/ 0.01 lux (B/W)	0.2 lux @ F1.2	0.6 lux @ F1.2	0.2 lux @ F1.2			0.2 lux @ F1.2	0.6 lux @ F1.2	0.2 lux @ F1.2			1 lux/ 0.1 lux (B/W)		0.5 lux/ 0.3 lux (B/W)	0.07 lux/ 0.01 lux (B/W)		0.05 lux/ 0.01 lux (B/W)
Compression	-	-	-	-	-	-	-	-	MPEG-4 & Motion JPEG				MPEG-4 & Motion JPEG				MPEG-4 & Motion JPEG							
Resolution (NTSC/PAL)	480 TVL	520TVL	520TVL	470TVL	470TVL	480TVL	480TVL	540TVL	VGA, QVGA, CIF & QCIF	4xVGA (1.3 Mpix), QVGA, CIF & QCIF			VGA, QVGA, CIF & QCIF	4xVGA (1.3 Mpix), QVGA, CIF & QCIF			D1 (4CIF), 1/2D1, 2CIF, CIF & QCIF							
Max. Frame rate:									30 / 25 @ VGA				30 / 25 @ VGA				30 / 25 @ D1							
MPEG-4									30 / 25 @ VGA				30 / 25 @ VGA				30 / 25 @ D1							
Motion JPEG									30 / 25 @ VGA				15 @ 4xVGA				30 / 25 @ VGA				15 @ 4xVGA			
Video Motion Detection	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Day & Night	-	-	-	Auto ICR					-	-	Auto ICR			-	-	Auto ICR			Auto ICR					
Wide Dynamic Range	-	-	-	-	-	-	-	●	-	-	-	●	-	-	-	●	-	-	-	-	-	-	●	
Alarm in/out	-	1x In / 1x Out	1x In / 1x Out	8x In / 1x Out					1x In / 1x Out				1x In / 1x Out				2x In / 1x Out							
Audio	-	-	-	-	-	-	-	-	1x In / 1x Out (full duplex)				1x In / 1x Out (full duplex)				1x In / 1x Out (full duplex)							
Mechanical / Electr. Image Flip	-	-	-	● / -	● / -	● / ●	● / ●	● / ●	-	-	-	-	-	-	-	-	● / -	● / -	● / -	● / ●	● / ●	● / ●	● / ●	
Privacy Mask	-	-	-	-	-	24	24	8	-	-	-	-	-	-	-	-	-	-	-	-	24	24	8	
Electronic image stabilizer	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	●	
Power over Ethernet	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	-	-	-	-	-	-	-	
Analog video output	●	●	●	●	●	●	●	●	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	
Security	-	-	-	-	-	-	-	-	Password protected web interface				Password protected web interface				Password protected web interface							
Vandal resistant	-	-	●	●	●	○	○	○	-	-	-	-	●	●	●	●	●	●	●	●	○	○	○	
Ingress Protection Rating	-	-	IP66	-	IP66	-	IP66	IP66	-	-	-	-	IP66	IP66	IP66	IP66	-	IP66	IP66	-	IP66	IP66		
Operating temperature	0 C to +50 C / +32 F to +122 F		-40 C to +50 C / -40 F to +122 F	0 C to +40 C / +32 F to +104 F	-30 C to +45 C / -22 F to +113 F	0 C to +40 C / +32 F to +104 F	-45 C to +50 C / -49 F to +122 F	-45 C to +50 C / -49 F to +122 F	0 C to +50 C / +32 F to +122 F				-40 C to +50 C / -40 F to +122 F				-10 C to +50 C / +14 F to +122 F							
Warranty	2 years		2 years	2 years				2 years				2 years				2 years								

● Standard ○ Optional