

tandard





A range of magnets that provides a wide number of options

TDSi offers a comprehensive range of electromagnetic door locking products that are suitable for a multitude of applications.

Featuring a 1200 lb holding force, these locks provide you with a cost effective, high security locking solution for your access control systems.

The standard range is available in both single and double formats, with or without lock monitoring, and is backed by a full range of complementary brackets.

All products are supplied in an attractive finish and are fast and easy to install.

standard magnets

SPECIFICATIONS

TDSi Part No.	2921-0202	2921-0203	2921-0206	2921-0207	
Format	Sin	Single		Double	
Monitored	No	Yes	No	Yes (single)	
Holding Force	120	1200 lb 2 x 1200 lb		200 lb	
Supply Voltage		12 V DC or 24 V DC (selectable)			
Nominal Current	500 mA (12 V DC) o	500 mA (12 V DC) or 250 mA (24 V DC)		1000 mA (12 VDC) or 500 mA (24 V DC)	
Connection		Fixed rising clamp type			
Lock Dimensions	41 x 266	41 x 266 x 67 mm		41 x 532 x 67 mm	
Armature Dimensions		16 x 185 x 61 mm			
Boxed Weight	4.9	4.9 kg		9.6 kg	

FEATURES & BENEFITS

Suitable for use in a wide-range of applications

This range of products offers you full flexibility in terms of installation through a comprehensive selection of locks and brackets.

Range of input voltages

These locks can be connected to either 12 V DC or 24 V DC power supplies allowing them to be used in all door locking applications.

No residual magnetism

Prevents the door from sticking shut when the lock is released.

Can be fitted to a variety of door thicknesses

The locks can be fitted to doors between 35 and 53mm thick.

Full range of mounting brackets available

Choose from a full range of brackets to suit your particular requirements.

Anodised aluminium housing

Provides an attractive and corrosion-resistant finish.

Armature kick-off button

Ensures that the armature plate dis-engages from the magnet immediately when the lock is released.


Safety bolt feature

Prevents the magnet from becoming detached from the top plate, eliminating the risk of personal injury from a falling magnet.

BRACKET OPTIONS







Z&L Bracket for inward opening doors

ORDERING INFORMATION

Part Number: 2921-0202

Description: Single standard door magnet

Part Number: 2921-0203

Description: Single standard door magnet with

lock monitoring

Part Number: 2921-0206

Description: Double standard door magnet

Part Number: 2921-0207

Description: Double standard door magnet with

lock monitoring feature

Part Number: 2921-0222

Description: L&Z bracket for standard door magnets for inward opening doors

4 Part Number: 2921-0223

Description: L bracket for standard door magnets

for outward opening doors

F Part Number: 2921-0225

Description: Surface mounted armature housing

for standard door magnets











TDSi UK Unit 10 Concept Park,

Innovation Close, Poole, Dorset BH12 4QT United Kingdom t: +44 (0)1202 723535 f: +44 (0)1202 724975 e: sales@tdsi.co.uk TDSi France

Immeuble ATRIA, 2 rue du Centre 93160 NOISY LE GRAND, France t: +33 (0)1 58 84 20 91 f: +33 (0)1 58 84 20 91 e: infos@tdsi-france.com TDSi China Rm 103, 1 Bld, Shangsha Inno

Shangsha Innovation Scier & Technology Park, 9283 Binhai Road, Futian District, Shenzhen 518048, P.R.China t: 86-755-82535725,

82535720 **f**: 86-755-82535770

f: 86-755-82535770 **e:** tdsiinfo@microgarde.com.cn