



An externally mountable magnet suitable for even the harshest environments

The TDSi external electromagnetic lock is a fully sealed unit which is suitable for applications that require a lock with a high level of ingress protection, such as securing gates.

Using the threaded connector on the end of the lock, the product can be interfaced directly to conduit to ensure that the integrity of the product sealing is maintained.

The external magnet can operate from both 12 V and 24 V, providing excellent flexibility.

external magnet

SPECIFICATIONS

TDSi Part No.	2921-0208
Format	Single
Monitored	Yes
Holding Force	1200 lb
Supply Voltage	12 V DC or 24 V DC (selectable)
Nominal Current	500 mA (12 V DC) or 250 mA (24 V DC)
Connection	Pre-wired cable (900 mm in length). Conduit gland is M24 x 3 (outside thread), M18 x 1.5 (inside thread)
Lock Dimensions	42 x 203 x 63 mm
Armature Dimensions	16 x 185 x 63 mm
Boxed Weight	4.7 kg

ORDERING INFORMATION

Part Number: 2921-0208

Description: External gate magnet

FEATURES & BENEFITS

Robust and Reliable

Designed to be used even in the harshest environments.

Range of Input Voltage

This lock can be connected to either 12 V DC or 24 V DC power supplies, allowing them to be used in all door locking applications.

Robust Stainless Steel Housing

High quality stainless steel construction makes this product highly corrosion resistant.

Armature Kick-Off Button

Ensures that the door unlocks immediately when the lock is released.

Complete with Cable

The product is supplied complete with 1 m of prewired cable, allowing straightforward installation.











TDSi UK Unit 10 Concept Park, Innovation Close, Poole, Dorset BH12 4QT United Kingdom

Dorset BH12 4QT United Kingdom t: +44 (0)1202 723535 f: +44 (0)1202 724975 e: sales@tdsi.co.uk TDSi France Immeuble ATRIA, 2 rue du Centre 93160 NOISY LE GRAND, France t: +33 (0)1 58 84 20 90 f: +33 (0)1 58 84 20 91

e: infos@tdsi-france.com

TDSi China Rm 103, 1 Bld, Shangsha Innovation Science & Technology Park, 9283 Binhai Road, Futian District, Shenzhen 518048, P.R.China t: 86-755-82535725, 82535720 f: 86-755-82535770

e: tdsiinfo@microgarde.com.cn