



MX763-HD



Key Features:

- 1/3" Sony IMX 035 CMOS sensor
- CS Mount
- 720p, 25fps
- Day / Night, Colour: 0.2 Lux; B/W: 0.1 Lux
- True day & night operation with auto IR-cut filter
- Power over Ethernet – IEEE 802.3af
- Independent HD recording stream



16:9 Wide Screen



4:3 Standard Resolution



MX763-HD Specification

MODEL	MX763-HD
	Day & Night Box Camera
	VIDEO
IMAGE SENSOR	1/3", Sony CMOS Sensor
RESOLUTION	1280 x 720 (720p)
FRAME RATE	Up to 25 fps
MINIMUM ILLUMINATION	0.1 Lux; Sens-up: 0.005 Lux
LENS	CS Mount
AUTO IR-CUT FILTER	Yes
VIDEO SETTINGS	brightness/contrast/saturation, mirroring, exposure, white balance, flickerless
	CONNECTIVITY
NETWORK INTERFACE	RJ-45, 10/100 base-T Ethernet (auto-sensing)
NETWORK PROTOCOL	HTTP, uPnP, DHCP
DYNAMIC IP	sureLINK, DDNS
RESOLUTION	1280x720, 960x540, 640x360, 320x180
FRAME RATE	Up to 25fps (AC 50 Hz); Up to 30 fps (AC 60Hz)
CONCURRENT USERS	6 (independent)
SECURITY	Multiple user access levels with password protection
WEB SERVER	Built-in
	VIDEO COMPRESSION
COMPRESSION	HD SMAC-M multi-stream
VIDEO STREAMING	4 independent streams for recording, LAN, Broadband and Mobile
	PC RECORDING
SOFTWARE	GX (Hardware) / sureREC (Software)
STREAM	Independent recording stream, independent resolution and frame rate
RECORDING MODE	Manual, schedule motion, schedule event
PLAYBACK	Forward, backward, pause, step forward, step backward, x10 fast forward, x25 fast forward
	EVENT HANDLING
EVENT	External alarm, video motion detection
ACTION	Dial back, alarm image recording at -3, 0, 3 seconds, email with JPEG attachment
EXTERNAL ALARM INPUT	1x, NC/NO
	POWER
POWER IN	DC 12V, PoE
MAX. RATING	12W (max)
	OPERATING ENVIRONMENT
AMBIENT TEMPERATURE	0°C - 40°C
RELATIVE HUMIDITY	<85% (no condensation)
	MECHANICAL DESIGN
WEATHER PROOF	IP66
NET WEIGHT	1.2 kg