

TeleEye RA Series feature-packed Digital Video Recorder



Brand	TeleEye
Model Code	RA204 / RA208 / RA216
Input Standard	PAL / NTSC, Composite video, 1 V _{p-p} , BNC
Input Channels	4 / 8 / 16
Recording Mode	Manual, Schedule, Event-driven
HDD Type	RA204 / RA208: SATA Interface; Internal x 1; RA216: SATA Interface; Internal x 2
MAX. RECORDING RATE	(P) : 25fps at 720 x 576 pixels; 100fps at 360 x 288 pixels (N) : 30fps at 720 x 480 pixels; 120fps at 360 x 240 pixels
Video Extraction	Network, USB
Network Interface	RJ-45, 10/100 Base-T Ethernet (auto-sensing), UPNP
Concurrent Users	2 (independent)
Web Server	Built-in
Telemetry Control Interface	Camera port: RS-422/485: 2-way terminal, asynchronous, 8 data bits, 1 stop bit, no parity, 2.4-19.2kbps.
USB Interface	High Speed USB2.0
Audio Input	2 channels, RCA, line level
Audio Output	Live / Playback: 1 channel, RCA, line level
Event	alarm, motion, video loss, disk full, hard disk failure
Action	recording, buzzer
External Alarm Inputs	4 x NC / NO
Relay Switch	1 Channel; Push-button / Latch; 24V AC, 1000mA
Power	RA204 / RA208: Voltage: 12V DC; Max. Rating: 30W RA216: Voltage: 12V DC; Max. Rating: 60W
Physical Specifications	Dimension (mm): RA204 / RA208: 230 x 242 x 65 RA216: 320 x 242 x 65 Weight (kg):

RA204: 1.5

RA208: 1.6

RA216: 2.2