



The Tomohawk DVR from Quick Solutions provides the very best in Digital Video Recording

For local real time display and stunning network viewing of up to 16 video images.

Product Benefits

- High Speed Recording of 100 frames per second for up to 16 cameras – ie. 25 fps for 4 cameras or 6 fps for 16 cameras.
- Real Time Display of ALL cameras 400 fps!
- Multi screen display in live and replay modes
- Extremely easy to set up and operate
- User definable set up of VMD, quality, speed etc
- Remote access via LAN, ISDN, PSTN etc
- Export still images to floppy
- Archive up to 600MB of video footage to CDR
- 3 spot video outputs
- Video Built in hardware watchdog for unattended operation
 - demIndustrial grade enclosure with managed cooling system
 - Fully expandable to suit every security requirement

www.quicksolutions.ltd.uk



DR16100-80 **High Speed Digital Video Recorder**

Spec sheet (Issue 1.S February 2002)

Hardware

4U rack mounted IPC 475mm deep Case 19" rack ears and blank plates included Accessories

Cooling Self managed multi fan cooling system with over temperature sensors

Colour Black enameled case

via 16x BNC or 2x high density connectors Video input 16x (2x real time, 1x realtime/replay) via BNC Video output 3х

Alarm input 16x (optional) (optional) Alarm output 4x

Main monitor SVGA monitor port 1x

Comms 2x RS232 Printer 1x Parallel

USB High speed USB 2x

Front mouse 1x Either front or rear mouse port

Access 1x Lockable front door TCP/IP 10/100M network port 1x

CDRW 16x10x40 buffer under-run protected CD archiver 1x

80GB Ultra EIDE Storage 1x

Floppy 1.44MB for storage of stills (JPEG)

Video

Compression MJPEG (Morgan) Display

Up to 400 FPS (real time x16) Up to 100 FPS (ie 4x25, or 16x6 etc) Recording Installation Auto camera detection and operation Auto record Record automatically enabled on start up

One touch record to enable recording of all cameras (override) O.T.R 16 user selectable zones per camera (with sensitivity control) V.M.D. Local and remote control of PTZ cameras (certain protocols) P.T.Z.

O.S.D Camera ID, Time and Date, recording activity.

Sequencer Sequencer control on/off

System Management

Watchdog Automatic monitoring and reset of system Security Password protected in selected areas ie Setup/Shutdown

Cooling Management of system cooling fans and 2x temperature sensors

Options

Backup Portable HDD for system backup (USB)

Alarm I/O see above

Upto 800GB internal storage Expansion R.A.I.D External R.A.I.D storage

Software

Local Video PLAYER software to replay archived footage on any PC

Remote CLIENT software to allow remote access of live and stored images Remote

Via PSTN / ISDN / TCP.IP

Environmental

-10 to 55 degrees C Temp range

Supply 240VAC Power 220W (max)

Quick Solutions

Carrington M31 4UG The Old School House Manchester Rd Manchester UK Tel 0161 776 0888 Fax 0161 776 0344 email sales@quicksolutions.ltd.uk

