

# HMD-TKWA-AES/CDA2

Mifare Keypad Reader

VANDERBILT



## Key Features include:

- Compact proximity reader complete with keypad
- Robust construction
- Suitable for internal and external applications
- VdS approved
- Compatible with the SPC system via SPCA210
- Wiegand interface

# HMD-TKWA-AES/CDA2

Mifare Keypad Reader

VANDERBILT

## ■ Technical data

System compatibility	SPC via CPCA210 interface
Interface to Controller	Wiegand
Supply voltage	12/24VDC
Current Consumption	26/40 mA
Tamper Switch	No
Card/Fob compatibility	Mifare Classic, Classic 4K, Ultralight, Ultralight C, light, mini & DESFire EV1
External Indications	Red, green & yellow LED
Cable	Factory fitted 4m of 10 core cable
Keypad	0 to 9, * & #
Operating temperature	-15°C to +65°C
Application	Internal or external
IP rating	IP65
Construction	
– Front plate	Black ABAS plastic
– Enclosure	Anodised aluminium
Environmental	Class IV
Dimensions (W x H x D)	50 x 160 x 25 mm
Approvals	VdS G115050

## ■ Accessories

Type	Art.-No.	Description	Weight
HMD-TS2-SW-S	N54547-Z101-A600	HMD-TS2-SW-S Mifare DESFire key fob	0.004Kg

## ■ Ordering Information

Type	Art.-No.	Description	Weight
HMD-TKWA-AES/CDA2	N54547-Z101-A400	HMD-TKWA-AES/CDA2 Mifare keypad reader Wiegand	0.590Kg