



PM500-GP

Access Control

Panel-mounted card reader

- **Compact proximity reader**
- **Fits most remote call point enclosures**
- **For both internal and external installations**

The PM500-GP reads Siemens unique Cotag cards and tags (both active and passive) which offers ultimate convenience and cost-efficiency. The PM500-GP is designed to fit most remote call point enclosures. It is supplied with a custom-machined perspex front panel for increased aesthetic appeal. It has a reading range of up to 23 cm with an active card and 8 cm with a passive card. Delivered without any configuration.

Onboard interface library supports popular clock&data and Wiegand interfaces. Interface set by using a configuration card. Distributor code/secondary code set by presenting a Cotag card containing the valid distributor code/secondary code.

Technical data

PM500-GP	
Interface to controller	Set by Configuration card
Operating voltage	10.6 to 32 VDC
Current consumption	33 mA @ 12V DC 35 mA @ 24V DC
Tamper switch	No
Card technology	Cotag
Card compatibility	Set by presenting card
Card read distance	Up to 23 cm with active card. Up to 8 cm with passive card.
Indicators	3 x LED (red/yellow/green) 1 x Buzzer
Keypad	No
Operating temperature	-30 to +50 °C
Environment	Indoor or outdoor use
IP rating	IP55
Housing	High impact polycarbonate outer casing, with encapsulated electronics
Colour	Black
Dimensions (W x H x D)	68 x 73 x 13.5 mm
Approval	CE
Accessories	None

Details for ordering

Type	Part no	Designation	Weight
PM500-GP	GBI:52-300	Panel-mounted card reader	0.15 kg

Issued by
Siemens AB
Security Products
International Headquarters
Englundavägen 7
SE-171 24 Solna
Tel. +46 8 629 0300

www.siemens.com/securityproducts

© 2011 Copyright by Siemens AB

Data and design subject to change without notice.
Supply subject to availability.

Document no. **A6V10330086**

Edition 05.2011