



## BM31

Access Control

### Single button door entry phone for PABX

- 
- Analog extension for the PABX system
  - Includes CCTV control and a tamper switch

The BM31 is used as an analog extension for the PABX internal tele-phone system. The Hotline function can be set up to call a single selected number, which is defined in the PABX. The BM31 also includes CCTV control and a tamper switch. Connected telephones must be able to generate a standard tone signal (DTMF).

## Technical data

---

<b>BM31</b>	
Interface	Two analog extension cables for PABX
Housing	Cast metal with stainless steel buttons and security lock. For flush mounting, use BB5 flush mounting kit.
Environment	Indoor or outdoor use. In very exposed locations, use SH3 or SH1 rain cover.
IP rating	IP54
Operating temperature	-35 to +50 °C. At 90% relative air humidity.
Operating voltage	12 to 24 VAC/DC
Current consumption	60 mA in standby
Dimensions (W x H x D)	80 x 200 x 40 mm
Calling time	Fixed 30 seconds
Code capacity	N/A
Inputs	Exit request (with delay). External control of calling. External control of ending call.
Outputs	Voltage-free relay contact, max. 2 A 28 VDC. Tamper switch for alarm (normally closed). Relay for control of CCTV system.
Opening time	Fixed 7 seconds

## Details for ordering

---

Type	Part no	Designation	Weight
BM31	S24246-C7901-A1	Single button door entry phone for PABX	1.3 kg

Issued by  
Bewator AB  
SE-171 24 Solna  
Sweden

[www.sbt.siemens.com](http://www.sbt.siemens.com)

© 2008 Copyright by  
Bewator AB, a Siemens company  
Data and design subject to change without notice.  
Supply subject to availability.

---

Document no. **A6V10081712**  
Edition 04.2008