



## BT44

Access Control

## Four call button door entry phone

---

- **Sturdy construction for outdoor use**

BT44 is a traditional doorphone with four keys. It connects by wire to up to four V801/B801 handsets.

## Technical data

---

<b>BT44</b>	
Interface	5-wire cable to handset
Housing	Cast metal with stainless steel keys and security lock. For flush mounting, use BB5 flush mounting unit.
Colour	Grey
Environment	Indoor or outdoor use (IP54 design). In very exposed locations, use SH3 or SH1 rain cover.
IP rating	IP54
Operating temperature	-35 to +50 °C. At 90% relative air humidity.
Operating voltage	12 to 24 VAC/DC
Current consumption	40 mA in standby
Dimensions (W x H x D)	80 x 200 x 40 mm
Door capacity	1
Code capacity	N/A
Inputs	N/A
Outputs	Voltage-free relay contact, max. 2 A 28 VDC. Control of separate CCTV system. Tamper switch for alarm (normally closed).
Opening time	1-15 seconds

## Details for ordering

---

Type	Part no	Designation	Weight
BT44	S24246-F8002-A1	Four call button door entry phone	1.3 kg

Issued by  
Bewator AB  
SE-171 24 Solna  
Sweden

[www.sbt.siemens.com](http://www.sbt.siemens.com)

© 2008 Copyright by  
Bewator AB, a Siemens company  
Data and design subject to change without notice.  
Supply subject to availability.

---

Document no. **A6V10081687**  
Edition 04.2008